

2 -	3
	3
	3
2 (ML2)	5
Linux bridge agent	6
Layer-3	7
DHCP	8

-
2
Last update: 2020/09/24 02:17
- https://atl.kr/dokuwiki/doku.php/%EB%84%A4%ED%8A%B8%EC%9B%8C%ED%82%B9_%EC%98%B5%EC%85%98_2_-_%EC%85%80%ED%94%84_%EC%84%9C%EB%B9%84%EC%8A%A4_%EB%84%A4%ED%8A%B8%EC%9B%8C%ED%81%AC
-

2 -

controller

```
[root@controller ~]# yum install openstack-neutron openstack-neutron-ml2 \
openstack-neutron-linuxbridge ebtables
```

1. /etc/neutron/neutron.conf

- [database] :

```
[database]
# ...
connection = mysql+pymysql://neutron:NEUTRON_DBPASS@controller/neutron
```

NEUTRON_DBPASS

[database] connection

- [DEFAULT] 2 (ML2) , IP :

```
[DEFAULT]
# ...
core_plugin = ml2
service_plugins = router
allow_overlapping_ips = true
```

- [DEFAULT] RabbitMQ :

```
[DEFAULT]
# ...
transport_url = rabbit://openstack:RABBIT_PASS@controller
```

RABBIT_PASS

- [DEFAULT] [keystone_authtoken] :

```
[DEFAULT]
# ...
auth_strategy = keystone

[keystone_authtoken]
# ...
www_authenticate_uri = http://controller:5000
auth_url = http://controller:5000
memcached_servers = controller:11211
auth_type = password
project_domain_name = default
user_domain_name = default
project_name = service
username = neutron
password = NEUTRON_PASS
```

NEUTRON_PASS *. [keystone_authtoken]*

- [DEFAULT] [nova] compute :

```
[DEFAULT]
# ...
notify_nova_on_port_status_changes = true
notify_nova_on_port_data_changes = true

[nova]
# ...
auth_url = http://controller:5000
auth_type = password
project_domain_name = default
user_domain_name = default
region_name = RegionOne
project_name = service
username = nova
password = NOVA_PASS
```

NOVA_PASS *. [oslo_concurrency]*

```
[oslo_concurrency]
# ...
lock_path = /var/lib/neutron/tmp
```

2 (ML2)

ML2 Linux 2 () 가

1. /etc/neutron/plugins/ml2/ml2_conf.ini

- [ml2] FLAT, VLAN, VXLAN

```
[ml2]
# ...
type_drivers = flat,vlan,vxlan
```

- [ml2] VXLAN

```
[ml2]
# ...
tenant_network_types = vxlan
```

- [ml2] Linux bridge L2-population :

```
[ml2]
# ...
mechanism_drivers = linuxbridge,l2population
```

ML2 type_drivers 가
.Linux bridge agent VXLAN

- [ml2] :

```
[ml2]
# ...
extension_drivers = port_security
```

- [ml2_type_flat] FLAT provider 가 :

```
[ml2_type_flat]
# ...
flat_networks = provider
```

- [ml2_type_vxlan] VXLAN

```
[ml2_type_vxlan]
# ...
vni_ranges = 1:1000
```

- [securitygroup] ipset :

```
[securitygroup]
# ...
enable_ipset = true
```

Linux bridge agent

Linux bridge agent 2 () 가

1. /etc/neutron/plugins/ml2/linuxbridge_agent.ini

- [linux_bridge] 가 :

```
[linux_bridge]
physical_interface_mappings = provider:PROVIDER_INTERFACE_NAME
```

PROVIDER_INTERFACE_NAME	Provider
• [vxlan] VXLAN	IP , L2-population

```
[vxlan]
enable_vxlan = true
local_ip = OVERLAY_INTERFACE_IP_ADDRESS
l2_population = true
```

OVERLAY_INTERFACE_IP_ADDRESS
IP
OVERLAY_INTERFACE_IP_ADDRESS IP

- [securitygroup] iptables :

DHCP

DHCP 가 DHCP .

1. /etc/neutron/dhcp_agent.ini

- [DEFAULT] , dnsmasq DHCP Provider 가 :

```
[DEFAULT]
# ...
interface_driver = linuxbridge
dhcp_driver = neutron.agent.linux.dhcp.Dnsmasq
enable_isolated_metadata = true
```

From: <https://atl.kr/dokuwiki/> - AllThatLinux!
Permanent link: https://atl.kr/dokuwiki/doku.php/%EB%84%A4%ED%8A%B8%EC%9B%8C%ED%82%B9_%EC%98%B5%EC%85%98_2_-_%EC%85%80%ED%94%84_%EC%84%9C%EB%B9%84%EC%8A%A4_%EB%84%A4%ED%8A%B8%EC%9B%8C%ED%81%AC
Last update: 2020/09/24 02:17

