

root , 3

..... 3

/etc/passwd 3

/etc/shadow 3

/etc/hosts 3

/etc/(x)inetd.conf 3

/etc/syslog.conf 4

/etc/services 4

SUID, SGID, Sticky bit 4

, 4

world writable 4

/dev device 4

\$HOME/.rhosts, hosts.equiv 4

IP 5

hosts.lpd 5

UMASK 5

..... 5

..... 6

..... 6

Last update: 2022/01/11 07:37 https://atl.kr/dokuwiki/doku.php/%ED%8C%8C%EC%9D%BC_%EB%B0%8F_%EB%94%94%EB%A0%89%ED%84%B0%EB%A6%AC_%EA%B4%80%EB%A6%AC?rev=1641886642

root ,

/etc/profile, ~/.bash_profile PATH “.”, “::”

```
(      ) PATH=.:$PATH:$HOME/bin
(      ) PATH=$PATH:$HOME/bin:.
```

가

```
find / -nouser -print
```

/etc/passwd

```
/etc/passwd
```

```
chmod 644 /etc/passwd chown root /etc/passwd
```

/etc/shadow

```
/etc/shadow
```

```
chmod 400 /etc/shadow chown root /etc/shadow
```

/etc/hosts

```
chmod 600 /etc/hosts chown root /etc/hosts
```

/etc/(x)inetd.conf

```
"/etc/xinetd.conf"      "/etc/xinetd.d/"      #chown root
/etc/xinetd.conf #chmod 600 /etc/xinetd.conf ※ "/etc/xinetd.d/"
```

/etc/syslog.conf

```
CentOS6 #chown root /etc/rsyslog.conf #chmod 640 /etc/rsyslog.conf
```

/etc/services

```
#chown root /etc/services #chmod 644 /etc/services
```

SUID, SGID, Sticky bit

```
Step 1) #chmod -s <file_name> Step 2) #find / -xdev -user root -type f  
( -perm -04000 -o -perm -02000 \) -exec ls -al {} \; Step 3)  
Setuid ( 가 )  
#/usr/bin/chgrp <group_name> <setuid_file_name> #/usr/bin/chmod 4750 <setuid_file_name>
```

```
 : “.profile”, “.kshrc”, “.cshrc”, “.bashrc”, “.bash_profile”, “.login”, “.exrc”,  
“.netrc” ls -l .bash_profile chmod o-w .bash_profile
```

world writable

```
world writable : 가 ( :  
rwxrwxrwx root root < >) find / -type f -perm -2 -exec ls -l {} \;  
chmod o-w <file name>
```

/dev device

```
find /dev -type f -exec ls -l {} \; major, minor number 가 device
```

\$HOME/.rhosts, hosts.equiv

```
ls -al /etc/hosts.equiv #chown root /etc/hosts.equiv #chmod 600 /etc/hosts.equiv  
“/etc/hosts.equiv” “$HOME/.rhosts” “ + ” #cat  
/etc/hosts.equiv (or $HOME/.rhosts)
```

IP

```

Step 1) vi "/etc/hosts.deny" ( ) Step 2)
      , (ALL Deny ) ( ) ( ) ALL:ALL Step 3) vi
      "/etc/hosts.allow" ( ) ( ) ( )
) sshd : 192.168.0.148, 192.168.0.6 ( ) < TCP Wrapper
가 >

```

SYSTAT, FINGER, FTP, TELNET, RLOGIN, RSH, TALK, EXEC, TFTP, SSH

< TCP Wrapper > /etc/hosts.deny -> IP

/etc/hosts.allow --> IP -->

RHEL 8

```

RHEL/CentOS 8 /etc/hosts.allow /etc/hosts.deny
libwrap . , 8 sshd
8 /etc/hosts.deny
OS firewalls . IP firewall-
cmd -permanent -add-source=10.10.10.10 IP firewall-cmd -permanent -remove-
source=10.10.10.10 IP firewall-cmd -permanent -add-source=10.10.10.0/24
firewall-cmd -permanent -add-port=80/tcp firewall-cmd -permanent -add-
port=1000-2000/tcp firewall-cmd -reload

```

<https://access.redhat.com/solutions/3935901>

hosts.lpd

```

Step 1) hosts.lpd #rm -rf /etc/hosts.lpd Step 2) (hosts.lpd
) #chmod 600 /etc/hosts.lpd Step 3) root (hosts.lpd ) #chown root
/etc/hosts.lpd

```

UMASK

umask /etc/profile umask 022 export umask

"/etc/passwd" #chown <user_name> <user_home_directory> #chmod o-w <user_home_directory>

passwd (" / ") 가 , 가
Step 1) 가 #userdel <user_name> Step 2) 가
#vi /etc/passwd #test:x:501:501:::/bin/bash (가 /
) #test:x:501:501::/home/test:/bin/bash (/ → /home/test)

#ls -al [] #find / -type d -name ".*" () Step 1) #find
/ -type f -name ".*" () Step 2) , -t

From: <https://atl.kr/dokuwiki/> - AllThatLinux!
Permanent link: https://atl.kr/dokuwiki/doku.php/%ED%8C%8C%EC%9D%BC_%EB%B0%8F_%EB%94%94%EB%A0%89%ED%84%B0%EB%A6%AC_%EA%B4%80%EB%A6%AC?rev=1641886642
Last update: 2022/01/11 07:37

