

root ,	3
	3
/etc/passwd	3
/etc/shadow	3
/etc/hosts	3
/etc/(x)inetd.conf	4
/etc/syslog.conf	4
/etc/services	4
SUID, SGID, Sticky bit	4
,	5
world writable	5
/dev device	5
\$HOME/.rhosts, hosts.equiv	5
IP	6
hosts.lpd	7
UMASK	7
	7
	8
	8

root ,

/etc/profile, ~/.bash_profile PATH “.”, “::”

```
(        ) PATH=.:$PATH:$HOME/bin  
(        ) PATH=$PATH:$HOME/bin:.
```

가

```
#find / -nouser -print
```

/etc/passwd

/etc/passwd

```
#chmod 644 /etc/passwd  
#chown root /etc/passwd
```

/etc/shadow

/etc/shadow

```
#chmod 400 /etc/shadow  
#chown root /etc/shadow
```

/etc/hosts

/etc/hosts

```
#chmod 600 /etc/hosts  
#chown root /etc/hosts
```

/etc/(x)inetd.conf

/etc/xinetd.conf /etc/xinetd.d/

```
#chown root /etc/xinetd.conf
#chmod 600 /etc/xinetd.conf
```

※ /etc/xinetd.d/

/etc/syslog.conf

CentOS6

```
#chown root /etc/rsyslog.conf
#chmod 640 /etc/rsyslog.conf
```

/etc/services

```
#chown root /etc/services
#chmod 644 /etc/services
```

SUID, SGID, Sticky bit

Step 1)

```
#chmod -s <file_name>
```

Step 2)

```
#find / -xdev -user root -type f \( -perm -04000 -o -perm -02000 \) -exec
```

```
ls -al {} \;
```

Step 3)

Setuid

(가)

```
#!/usr/bin/chgrp <group_name> <setuid_file_name>
#!/usr/bin/chmod 4750 <setuid_file_name>
```

,

```
: .profile, .kshrc, .cshrc, .bashrc, .bash_profile, .login, .exrc,
.netrc
```

```
#ls -l .bash_profile
#chmod o-w .bash_profile
```

world writable

```
world writable : 가 ( :
rwxrwxrwx root root < >)
```

```
#find / -type f -perm -2 -exec ls -l {} \;
#chmod o-w <file name>
```

/dev device

```
#find /dev -type f -exec ls -l {} \;
major, minor number 가 device
```

\$HOME/.rhosts, hosts.equiv

```
#ls -al /etc/hosts.equiv
#chown root /etc/hosts.equiv
#chmod 600 /etc/hosts.equiv
```

```
/etc/hosts.equiv $HOME/.rhosts +
```

```
#cat /etc/hosts.equiv (or $HOME/.rhosts)
```

IP

```
Step 1) vi /etc/hosts.deny ( )
```

```
Step 2) , (ALL Deny )
```

```
( )
( ) ALL:ALL
```

```
Step 3) vi /etc/hosts.allow ( )
```

```
( )
( ) sshd : 192.168.0.148, 192.168.0.6
```

```
( ) < TCP Wrapper 가 >
```

```
SYSTAT, FINGER, FTP, TELNET, RLOGIN, RSH, TALK, EXEC, TFTP, SSH
```

```
< TCP Wrapper > /etc/hosts.deny ->
IP /etc/hosts.allow -> IP
```

```
-->
```

RHEL 8

```
RHEL/CentOS 8 /etc/hosts.allow /etc/hosts.deny
```

```
, 8 sshd libwrap OS firewalls 8
/etc/hosts.deny
```

```
IP
#firewall-cmd --permanent --add-source=10.10.10.10
IP
#firewall-cmd --permanent --remove-source=10.10.10.10
IP
#firewall-cmd --permanent --add-source=10.10.10.0/24

#firewall-cmd --permanent --add-port=80/tcp

#firewall-cmd --permanent --add-port=1000-2000/tcp

#firewall-cmd --reload
```

<https://access.redhat.com/solutions/3935901>

hosts.lpd

```
Step 1) hosts.lpd
#rm -rf /etc/hosts.lpd
Step 2)          (hosts.lpd          )
#chmod 600 /etc/hosts.lpd
Step 3)      root      (hosts.lpd      )
#chown root /etc/hosts.lpd
```

UMASK

```
umask          /etc/profile
```

```
umask 022
export umask
```

```
/etc/passwd
```

```
#chown <user_name> <user_home_directory>
#chmod o-w <user_home_directory>
```

/etc/passwd 가 , 가 (/) 가

```
Step 1) 가
#userdel <user_name>
Step 2) 가
#vi /etc/passwd
#test:x:501:501:::/bin/bash ( 가 / )
#test:x:501:501::/home/test:/bin/bash ( / -> /home/test)
```

```
#ls -al [ ]
#find / -type f -name ".*" ( )
#find / -type d -name ".*" ( )
```

Step 1) -t Step 2) ,

