

RHEL 6 3
 Step 1 : 3
 Step 2 : 3
RHEL 7 3
 Step 1 : 3
 Step 2 : 4

RHEL 6

Step 1 :

```
[root@server ~]# hostname  
server
```

```
[root@server ~]# cat /etc/sysconfig/network | grep HOSTNAME  
HOSTNAME=server
```

Step 2 :

•

```
[root@server ~]# vim /etc/sysconfig/network  
HOSTNAME=
```

•

```
[root@server ~]# hostname  
[root@server ~]# echo > /proc/sys/kernel/hostname
```

RHEL 7

Step 1 :

```
[root@server ~]# hostnamectl  
[root@server ~]# hostnamectl  
  Static hostname: server  
    Icon name: computer-vm  
    Chassis: vm  
  Machine ID: 1ccb951fbb4644d8813826bcb450f1bb  
    Boot ID: 962941d25a6c4065a919ace6c0f0c750  
  Virtualization: vmware  
  Operating System: CentOS Linux 7 (Core)  
    CPE OS Name: cpe:/o:centos:centos:7  
    Kernel: Linux 3.10.0-123.el7.x86_64  
  Architecture: x86_64
```

Last update: 2015/06/18 15:49 https://at1.kr/dokuwiki/doku.php/%ED%98%B8%EC%8A%A4%ED%8A%B8%EB%AA%85_%EB%B3%80%EA%B2%BD?rev=1433730568

```
[root@server ~]# hostname  
server
```

Step 2 :

```
[root@server ~]# hostnamectl set-hostname client
```

From: <https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link: https://at1.kr/dokuwiki/doku.php/%ED%98%B8%EC%8A%A4%ED%8A%B8%EB%AA%85_%EB%B3%80%EA%B2%BD?rev=1433730568

Last update: 2015/06/18 15:49

