

- Apache HTTPD** 3
- Method** 3
- Apache httpd logfile permission(umask)** 3
- rpm 3
- envvars 3
- apachectl 4
- Host Header Poisoning / Injection** 4
- 5

Apache HTTPD

Method

```
<Location "/*">
  <LimitExcept GET POST>
    Order deny,allow
    Deny from all
  </LimitExcept>
</Location>
```

Apache httpd logfile permission(umask)

644 . umask umask가 0022

rpm

rpm /etc/sysconfig/httpd 가 .

```
umask 0027
```

envvars

rpm . apache apachectl
 envvars . ()

```
# pick up any necessary environment variables
if test -f /APP/httpd-2.4.39/bin/envvars; then
  . /APP/httpd-2.4.39/bin/envvars
fi
```

envvars envvars umask 가

```
umask 0027 #<- 4 .
```

apachectl

```
apachectl envvars (Redhat JBCS(Jboss core services)  
) apachectl umask .
```

```
umask 0027 #<- 4 .
```

```
umask .
```

Host Header Poisoning / Injection

HTTP Host Header www.example.com
example.com

- **Apache HTTPD**

```
RewriteEngine On  
RewriteCond %{HTTP_HOST} !^(www.example.com|example.com)$ [NC]  
RewriteRule .* - [F]
```

```
VirtualHost .
```

```
<VirtualHost _default_:*>  
DocumentRoot /www/default  
</VirtualHost>
```

- **JBoss EAP 7** Undertow expression-filter

```
/subsystem=undertow/configuration=filter/expression-filter=host-  
checker:add(expression="not(equals(%{i,Host}, www.example.com) or  
equals(%{i,Host}, example.com)) -> response-code(403)")  
/subsystem=undertow/server=default-server/host=default-host/filter-ref=host-  
checker:add
```

```
xml .
```

```
<subsystem xmlns="urn:jboss:domain:undertow:3.1">
```

```

<buffer-cache name="default"/>
<server name="default-server">
    ...
    <host name="default-host" >
        ...
        <filter-ref name="host-checker"/>
    </host>
</server>
<filters>
    ...
    <expression-filter name="host-checker"
expression="not(equals(%{i,HOST}, www.example.com) or equals(%{i,HOST},
example.com)) -> response-code(403)"/>
</filters>
</subsystem>

```

- **JBoss EAP 6** rewrite

```

<subsystem xmlns="urn:jboss:domain:web:2.1" default-virtual-server="default-
host" native="false">
    <connector name="http" protocol="HTTP/1.1" scheme="http" socket-
binding="http"/>
    <connector name="ajp" protocol="AJP/1.3" scheme="http" socket-
binding="ajp"/>
    <virtual-server name="default-host" enable-welcome-root="true">
        <alias name="localhost"/>
        <alias name="example.com"/>
        <!-- added -->
        <rewrite pattern="^(.*)$" substitution="-" flags="F">
            <condition test="%{HTTP:HOST}"
pattern="!(www.example.com|example.com)" flags="NC"/>
        </rewrite>
    </virtual-server>
</subsystem>

```

- <https://access.redhat.com/solutions/3166341>
- <https://access.redhat.com/solutions/3057511>

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/apache_httpd_%EB%B3%B4%EC%95%88%EC%B7%A8%EC%95%BD%EC%A0%90_%EC%A0%90%EA%B2%80?rev=1634708541

Last update: 2021/10/20 05:42

