

- ATS** ..... 3
- Forward Proxy** ..... 3
- ..... 3
- Reverse Proxy** ..... 3
- ..... 3
- ..... 4
- ..... 4
- ..... 4



# ATS

ATS

- record.config
- storage.config cache.config
- ip\_allow.yaml
- remap.config
- parent.config
- hosting.config, logging.yaml, sni.yaml, socks.config, strategies.yaml, splitdns.config, volume.config

## Forward Proxy

Forward Proxy

record.config

```
CONFIG proxy.config.url_remap.remap_required INT 0
```

- <https://docs.trafficserver.apache.org/en/latest/admin-guide/configuration/transparent-forward-proxying.en.html>

## Reverse Proxy

ip\_allow.yaml

) 123.12.3.0 ~ 123.12.3.123

ip\_allow.yaml

```
apply: in
ip_addrs: 123.12.3.000-123.12.3.123
action: allow
```

) 192.168.1.0/24, 172.16.0.0/20, 10.0.0.0/8  
ip\_allow.yaml

```
apply: in
```

```
ip_addrs:  
- 10.0.0.0/8  
- 172.16.0.0/20  
- 192.168.1.0/24  
action: deny
```

- [https://docs.trafficserver.apache.org/en/latest/admin-guide/files/ip\\_allow.yaml.en.html](https://docs.trafficserver.apache.org/en/latest/admin-guide/files/ip_allow.yaml.en.html)

ATS storage.config  
DISK Cache 1G 10MB 가

DISK Cache

storage.config

```
/var/cache/trafficserver 256M
```

RAW

```
# Examples: Using 0_DIRECT on disks (Linux kernel >= 2.6.3, FreeBSD > 5.3)  
#  
/dev/disc/by-id/[Insert_ID_Here_12345] # Linux  
/dev/disc/by-path/[Insert-Path-Here:12:34:56-1.0.0.0] # Linux
```

- <https://docs.trafficserver.apache.org/en/latest/admin-guide/storage/index.en.html>

From:  
<https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link:  
[https://at1.kr/dokuwiki/doku.php/ats\\_%EC%84%A4%EC%A0%95\\_%EB%B0%A9%EB%B2%95?rev=1714618296](https://at1.kr/dokuwiki/doku.php/ats_%EC%84%A4%EC%A0%95_%EB%B0%A9%EB%B2%95?rev=1714618296)

Last update: 2024/05/02 02:51

