

baremetal node get system uuid 3
..... 3

baremetal node get system uuid

```
$ openstack baremetal introspection data save
9dcc87ae-4c6d-4ede-81a5-9b20d7dc4a14 | jq .extra.system.product.uuid
"F5055C6C-477F-47FB-AFE5-95C6928C407F"
```

heat template

```
resource_registry:
  OS::TripleO::ComputeExtraConfigPre: /usr/share/openstack-tripleo-heat-
  templates/puppet/extraconfig/pre_deploy/per_node.yaml
parameter_defaults:
  NodeDataLookup: '{"F5055C6C-477F-47FB-AFE5-95C6928C407F":
{"nova::compute::vcpu_pin_set": [ "2", "3" ]}}'
```

NIC

```
resource_registry:
  OS::TripleO::NodeUserData: /usr/share/openstack-tripleo-heat-
  templates/firstboot/os-net-config-mappings.yaml
parameter_defaults:
  NetConfigDataLookup:
    control0:
      dmiString: 'system-uuid'
      id: 'd1259a88-6d31-11ec-860f-3a68dd6cbf33'
      nic1: "enp1s0"
      nic2: "enp2s0"
      nic3: "enp3s0"
      nic4: "enp9s0"
      nic5: "enp10s0"
```

- https://access.redhat.com/documentation/en-us/red_hat_openstack_platform/13/html/advanced_overcloud_customization/chap-configuration_hooks

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/baremetal_node_get_system_uuid

Last update: **2022/08/30 05:14**



