

- btrfs** **No-HDD PC** 3
- 0. 3
- 1. 3
- 2. 3
- 3. ISCSI** 4
- 4. *가* **DHCP, TFTP, gPXE** 5

btrfs

No-HDD PC



: http://2cpu.co.kr/bbs/board.php?bo_table=vm&wr_id=2343

0.

btrfs file system

/iscsi ←-

- DHCP
- TFTP
- ISCSI
- BTRFS

1.

IP

```
/etc/network/interface
auto eth0
iface eth0 inet static
    address 211.168.0.3
    netmask 255.255.255.0
    gateway 211.168.0.1
    dns-nameservers 168.124.101.2
```

2.

가 ..

```
* # DHCP
```

```
root:/#apt-get install isc-dhcp-server
```

```
* #TFTP
```

```
root:/#apt-get install xinetd
root:/#apt-get install tftpd
root:/#apt-get install hpa-tfpd
```

- #BTRFS-TOOLS

```
root:/#apt-get install btrfs-tools
```

- #iscsi

```
root:/#apt-get install iscsitarget iscsitarget-dkms
```

3. ISCSI

```
ISCSI TARGET
```

```
가
```

```
..
```

```
100G 가
```

```
BTRFS
```

```
100G
```

```
/iscsi
```

```
50%
```

```
full
```

```
가
```

```
root:/# mkdir /iscsi/image
root:/# chmod 755 /iscsi/image
root:/# btrfs subvolume create /iscsi/image/win7
root:/# chmod 755 /iscsi/image/win7
```

```
root:/# dd if=/dev/zero of=/iscsi/image/win7/win7.img bs=1048576
count=500000
```

```
50 가
```

```
* /etc/default/iscsitarget
```

```
ISCSITARGET_ENABLE=true --- > true
```

- /etc/iet/ietd.conf

```
Target iqn.2014-08.vitamin.com:master -----> iscsi target
  Lun 0 Path=/iscsi/image/win7/win7.img,Type=fileio -----> iscsi target
image path
Alias client1 --> 가
MaxConnections 1 -----> iscsi
```

- Iscsi target

```
root:/# service iscsitarget restart
```

ok

4. 가 DHCP, TFTP, gPXE

<http://rom-o-matic.net/gpxe/gpxe-1.0.1/contrib/rom-o-matic/> undionly.kpxe ..

* dhcp

```

/etc/dhcp/dhcpd.conf
subnet 211.168.0.0 netmask 255.255.255.0 {
range dynamic-bootp 211.168.0.11 211.168.0.185;
option domain-name-servers 164.124.101.2, 168.126.63.1;
option broadcast-address 211.168.0.255;
option routers 211.168.0.1;
authoritative;
}
host client1 {
hardware ethernet 00:00:00:00:00:00; ----->
fixed-address 192.168.0.10; ----->
option host name "client1";
if exists user-class and option user-class = "gPXE" {
filename "";
option root-path "iscsi:211.168.0.3::::iqn.2014-08.vitamin.com:master";
-- > iscsi target
} else {
filename "gpxe.kpxe";
}
}

```

가	Boot from LAN	Enable	..	CMOS SETUP	가
				NETWORK	1

- TFTP

/etc/xinetd.d/tftp

```

service tftp
{
disable = no --- > yes no
socket_type = dgram
protocol = udp
wait = yes
user = nobody
server = /usr/sbin/in.tftpd
server_args = -s /tftpboot
}

```

#####

gpxe-1.0.1-undionly.kpxe /tftpboot gpxe.kpxe

/tftpboot . #mkdir /tftpboot .

- DHCP

```
root:/#service isc-dhcp-server restart
```

... 가 . 10 100

```
btrfs subvolume snapshot /iscsi/image/win7 /iscsi/image/pc01
btrfs subvolume snapshot /iscsi/image/win7 /iscsi/image/pc02
btrfs subvolume snapshot /iscsi/image/win7 /iscsi/image/pc03
```

pc . /iscsi/image/pc01/ win7.img 가
pc /etc/iet/ietd.conf 가

```
Target iqn.2014-08.vitamin.com:pc01
Lun 0 Path=/iscsi/image/pc01/win7.img,Type=fileio
MaxConnecions 1
Target iqn.2014-08.vitamin.com:pc02
Lun 0 Path=/iscsi/image/pc02/win7.img,Type=fileio
MaxConnecions 1
Target iqn.2014-08.vitamin.com:pc03
Lun 0 Path=/iscsi/image/pc03/win7.img,Type=fileio
MaxConnecions 1
```

dhcp /etc/dhcp/dhcpd.conf 가 .
/etc/dhcp/dhcpd.conf

```
subnet 211.168.0.0 netmask 255.255.255.0 {
  range dynamic-bootp 211.168.0.11 211.168.0.185;
  option domain-name-servers 164.124.101.2, 168.126.63.1;
  option broadcast-address 211.168.0.255;
  option routers 211.168.0.1;
  authoritative;
}
host master {
  hardware ethernet 00:00:00:00:00:00;
  fixed-address 211.168.0.10;
  option host name "client1";
  if exists user-class and option user-class = "gPXE" {
    filename "";
    option root-path "iscsi:211.168.0.3::::iqn.2014-08.vitamin.com:master";
```

```

} else {
    filename "gpxe.kpxe";
}
}
host pc01 {
    hardware ethernet 00:00:00:00:00:00;
    fixed-address 211.168.0.11;
    option host name "pc01";
    if exists user-class and option user-class = "gPXE" {
        filename "";
        option root-path "iscsi:211.168.0.3::::iqn.2014-08.vitamin.com:pc01";
    } else {
        filename "gpxe.kpxe";
    }
}
host pc02 {
    hardware ethernet 00:00:00:00:00:00;
    fixed-address 211.168.0.12;
    option host name "pc02";
    if exists user-class and option user-class = "gPXE" {
        filename "";
        option root-path "iscsi:211.168.0.3::::iqn.2014-08.vitamin.com:pc02";
    } else {
        filename "gpxe.kpxe";
    }
}
host pc03 {
    hardware ethernet 00:00:00:00:00:00;
    fixed-address 211.168.0.13;
    option host name "client1";
    if exists user-class and option user-class = "gPXE" {
        filename "";
        option root-path "iscsi:211.168.0.3::::iqn.2014-08.vitamin.com:pc03";
    } else {
        filename "gpxe.kpxe";
    }
}
}

```

```

pc01          iscsi          path          tftp          iscs
pc01          .
pc01

```

```

#ietadm --op delete --tid=1 --lun=0 iscsi
#btrfs subvolume delete /iscsi/image/pc01
#btrfs subvolume snapshot /iscsi/image/win7 /iscsi/image/pc01

#ietadm --op new --tid=1 --lun=0 --params Path=/iscsi/image/pc01/win7.img
iscsi

```

0.1 가 가 . 가
master 가 pc
. master pc
master, pc01, pc02 pc03, master iscsi 가 ip
iscsi

<http://support.microsoft.com/kb/2550978> <http://support.microsoft.com/kb/976042/>

From: <https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link: https://at1.kr/dokuwiki/doku.php/btrfs%EB%A5%BC_%EC%9D%91%EC%9A%A9%ED%95%9C_no-hdd_pc%EB%B0%A9_%EA%B5%AC%EC%B6%95?rev=1425452016

Last update: 2015/06/18 15:49

