

- Ceph Configuration** 3
- Ceph Runtime configuration*** 3
- Setting a Specific Configuration Setting at Runtime*** 3
- 4

Ceph Configuration

Ceph Runtime configuration

```
# ceph daemon {daemon-type}.{id} config show
ex) ceph daemon osd.0 config show
```



가

OSD

OSD

```
# ceph daemon {daemon-type}.{id} config get {parameter}
ex) ceph daemon osd.0 config get public_addr
```

Setting a Specific Configuration Setting at Runtime

ceph

2가

1. Ceph Monitor
2. Administration Socket

```
tell injectargs
```

Ceph

```
# ceph tell {daemon-type}.{daemon id or *} injectargs --{name} {value} [--{name} {value}]
```

```
ex) ceph tell osd.0 injectargs '--debug-osd 0/5'
```

tell

```
  --{config_opt} {opt-val} 가 가
```

. daemon

가

ceph tell

monitor

가

```
# sudo ceph osd.0 config set debug_osd 0/5
```

- https://access.redhat.com/documentation/en-us/red_hat_ceph_storage/3/html/configuration_guide/configuration_reference

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/ceph_configuration

Last update: **2021/08/24 03:03**

