

Ceph openstack 3

Ceph openstack

```
##### Ceph Pool
[root@ceph ~]# ceph osd pool create volumes 16
[root@ceph ~]# ceph osd pool create images 16
[root@ceph ~]# ceph osd pool create vms 16
[root@ceph ~]# ceph osd pool create backups 16
[root@ceph ~]# ceph osd pool create metrics 16
[root@ceph ~]# ceph osd pool create gnocchi 16

[root@ceph1 ~]# ceph osd pool application enable volumes rbd
enabled application 'rbd' on pool 'volumes'
[root@ceph1 ~]# ceph osd pool application enable images rbd
enabled application 'rbd' on pool 'images'
[root@ceph1 ~]# ceph osd pool application enable vms rbd
enabled application 'rbd' on pool 'vms'
[root@ceph1 ~]# ceph osd pool application enable backups rbd
enabled application 'rbd' on pool 'backups'
[root@ceph1 ~]# ceph osd pool application enable metrics rbd
enabled application 'rbd' on pool 'metrics'
[root@ceph1 ~]# ceph osd pool application enable gnocchi rbd
enabled application 'rbd' on pool 'gnocchi'

##### CephFS
[root@ceph ~]# ceph osd pool create manila_data 16
[root@ceph ~]# ceph osd pool create manila_metadata 16

##### client.openstack
[root@ceph ~]# ceph auth add client.openstack mgr 'allow *' mon 'profile
rbd' osd 'profile rbd pool=volumes, profile rbd pool=vms, profile rbd
pool=images, profile rbd pool=backups, profile rbd pool=metrics, profile rbd
pool=gnocchi, profile rbd pool=manila_data, profile rbd
pool=manila_metadata'

ceph auth add client.glance mgr 'allow *' mon 'profile rbd' osd 'profile rbd
pool=images'
ceph auth add client.cinder mgr 'allow *' mon 'profile rbd' osd 'profile rbd
pool=volumes'
ceph auth add client.cinder-backup mgr 'allow *' mon 'profile rbd' osd
'profile rbd pool=backups'
ceph auth add client.nova mgr 'allow *' mon 'profile rbd' osd 'profile rbd
pool=vms'
ceph auth add client.gnocchi mgr 'allow *' mon 'profile rbd' osd 'profile
rbd pool=gnocchi'
ceph auth add client.manila mgr 'allow *' mon 'profile rbd' osd 'profile rbd
pool=manila_data, profile rbd pool=manila_metadata'

[root@ceph ~]# ceph auth list
client.openstack
```

```
key: AQDL+/9gCTn9FBAAhImovklrAThK9Q30+Dg9CA==
caps: [mgr] allow *
caps: [mon] profile rbd
caps: [osd] profile rbd pool=volumes, profile rbd pool=vms, profile rbd
pool=images, profile rbd pool=backups, profile rbd pool=metrics
```

CephFS

```
[root@ceph ~]# ceph auth add client.manila mon 'allow r, allow command "auth
del", allow command "auth caps", allow command "auth get", allow command
"auth get-or-create"' osd 'allow rw' mds 'allow *' mgr 'allow *'
```

```
[root@ceph ~]# ceph auth get-key client.manila
AQDQ991cAAAAABAA0aXFrTnjH9a039P0iVvYyg==
```

```
[root@ceph01 ~]# ceph auth get client.cinder -o
/etc/ceph/ceph.client.cinder.keyring
```

From: <https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link: https://at1.kr/dokuwiki/doku.php/ceph_openstack_%EB%B3%BC%EB%A5%A8_%EB%B0%8F_%EA%B3%84%EC%A0%95_%EC%84%A4%EC%A0%95

Last update: 2024/03/27 02:27

