

- Cisco Switch** 3
- ROMMON Mode** 3
- 3
- 3
- IP** 4
- Timestamp** 4
- 4
- DNS** 6
- 7

Cisco Switch

: <https://cdn.technet24.ir/Downloads/Cisco/IOS/>

ROMMON Mode

Rommon mode mode

rommon mode

가 BAUD RATE

```
switch: set BAUD 115200
//
switch: set
BAUD=115200
...
```

	VLAN	가	vlan.dat	delete vlan.dat
erase start				reload
reload			no	

```
#del vlan.dat
#erase start
#reload
no
```

```
switch#>show version //
switch#>show interface vlan //
switch#>show running-config //
```

```
R1# show flash -> Flash
R1# show ip route ->
R1# show ip interface brief ->
R1# show interface [Interface Name] ->
R1# show controllers [Interface Name] ->
```

```
R1# show cdp neighbor ->
R1# show cdp neighbor detail -> IP
R1# show running-config -> Running-Config (RAM)
R1# show startup-config -> Startup-Config (NVRAM)
R1# copy running-config startup-config -> RAM NVRAM
R1# erase startup-config -> NVRAM
```

IP

```
Switch# configure terminal
Switch(config)# interface vlan 1
Switch(config-if)# ip address 192.168.1.2 255.255.255.0
Switch(config-if)# no shutdown
Switch(config-if)# exit
Switch(config)# ip default-gateway 192.168.1.1
```

```
DHCP          1.          interface vlan 1          VLAN 1
. 2. ip address dhcp          IP          . 3. no shutdown
VLAN 1 가          . 4
.
가          dhcp IP          show running-config          IP
.          show dhcp lease          show interface vlan 1          IP
```

Timestamp

```
# conf t
(config) # service timestamps debug datetime localtime // debug
(config) # service timestamps log datetime localtime // log
```

```
# sh clock //
# clock set 13:13:13 april 20 2020 //
# clock timezone kst 9 // ( )

# conf t
(config) # ntp server time.bora.net // NTP (boranet)
# sh ntp status // NTP
```

-

가

```
gmate(config)# line 0 16
gmate(config-line)# logg sync
```

-

```
gmate(config)#line console 0
gmate(config-line)# exec-timeout 0
```

-

```
gmate(config)# enable secret switch
```

switch

-

```
gmate#show line
```

VTY

```
gmate(config)#line vty 0 15
gmate(config-line)# password switch
```

0~ 15

가 switch

-

```
gmate#show runnign-config
```

- vty

```
gmate(config)#service password-encryption
```

-

```
gmate(config)#banner motd *
```

```
Authorized access only!!
```

```
*
```

```
*
```

```
•
```

```
gmate(config)# default-value exec-character-bits 8
gmate(config)# banner motd *
가 !!
*
gmate(config)#
```

```
•
```

```
gmate(config)# interface f 1/0/1
gmate(config)# description gmatel
gmate(config)# interface f 1/0/2
gmate(config)# description gmate2
```

```
•
```

```
enable
config terminal
no ip domain-lookup
enable secret $gm@te2oo8

alias exec c config terminal
alias exec r show running-config
alias exec i show ip route
alias exec b show ip interface breif

line consol 0
logging synch
exec-timeout 0
lin vty 0 5
pass $gm@te2oo8
exit
hostname
```

DNS

```
cisco(config)#
cisco(config)#ip domain-lookup
cisco(config)#ip name-server 210.20.64.21
```

-

```
cisco(config)# no ip domain-lookup
```

- stp

```
Switch# show spanning-tree  
Switch# show spanning-tree vlan [num]  
Switch# show spanning-tree vlan [num] detail
```

-

```
Switch# show interface status
```

- link aggregation

```
Switch(config)# int port-channel 1  
Switch(config-if)# int range gi 1/0/5-6  
// chnnel-group 1 mode on  
channel-group 1 mode active  
  
Switch(config-if)# channel-proto lacp  
Switch(config-if)# exit  
  
Switch(config)# int port-channel 1  
Switch(config-if)# switchport mode access  
Switch(config-if)# switchport access vlan 10  
  
Switch# show lacp neighbor
```

From:
<https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://at1.kr/dokuwiki/doku.php/cisco_switch_%EC%84%A4%EC%A0%95?rev=1650631325

Last update: **2022/04/22 12:42**

