

**cups-browsed apparmor error** ..... 3  
..... 3  
..... 3



# cups-browsed apparmor error

```
dmesg journal cups-browsed apparmor 가 가 .
Linux AppArmor (denied)
AppArmor MAC(Mandatory Access Control) ,
/usr/sbin/cups-browsed 가 Unix (Unix domain socket)
1 ) 가 .
AppArmor RHEL selinux .
```

```
kernel: audit: type=1400 audit(1761181340.544:699): apparmor="ALLOWED"
operation="setsockopt" class="net" info="failed protocol match" error=-13
profile="/usr/sbin/cups-browsed" pid=1210 comm="cups-browsed" family="unix"
sock_type="stream" protocol=0 requested="setopt" denied="setopt" addr=none
```

```
/etc/apparmor.d/usr.sbin.cups-browsed 가 .
```

```
# 가
# Unix
unix (create, bind, listen, connect) type=stream,
```

```
systemctl restart cups-browsed.service
가
```

From:  
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:  
[https://atl.kr/dokuwiki/doku.php/cups-browsed\\_apparmor\\_error](https://atl.kr/dokuwiki/doku.php/cups-browsed_apparmor_error)

Last update: **2025/10/23 01:07**

