목차

DHCP 서버를 특정 인터페이스에서만 서비스 3
RHEL/CentOS 6 이전버전 3
RHEL/CentOS 7, 8 이후버전 3

DHCP 서버를 특정 인터페이스에서만 서비스

RHEL/CentOS 6 이전버전

`/etc/sysconfig/dhcpd` 파일 내에 아래 파라메터 추가

```
DHCPDARGS="eth0 eth1";
```

- https://access.redhat.com/documentation/en-us/red_hat_enterprise_linux/6/html/deployment_guide/sect-configuring_a_multihomed_dhcp_server

RHEL/CentOS 7, 8 이후버전

RHEL/CentOS 7, 8 이후버전에서는 `/etc/sysconfig/dhcpd` 파일에 설정하면 안 된다.

먼저 `/usr/lib/systemd/system/dhcpd.service` 파일을 `/etc/systemd/system/` 디렉토리로 복사한다.

```
# cp /usr/lib/systemd/system/dhcpd.service /etc/systemd/system/
```

그 다음 복사한 파일을 아래 내용처럼 수정한다. `enp0s1`과 `enp7s0`인터페이스에서만 서비스 하고 싶은 경우

```
ExecStart=/usr/sbin/dhcpd -f -cf /etc/dhcp/dhcpd.conf -user dhcpd -group
dhcpd --no-pid $DHCPDARGS enp0s1 enp7s0
```

이후 데몬을 리로딩하여 재시작한다.

```
# systemctl daemon-reload
# systemctl restart dhcpd.service
```

- https://access.redhat.com/documentation/en-us/red_hat_enterprise_linux/8/html/configuring_and_managing_networking/providing-dhcp-services_configuring-and-managing-networking

From:
https://atl.kr/dokuwiki/ - **AllThatLinux!**

Permanent link:
https://atl.kr/dokuwiki/doku.php/dhcp_%EC%84%9C%EB%B2%84%EB%A5%BC_%ED%8A%B9%EC%A0%95_%EC%9D%B8%ED%84%B0%ED%8E%98%EC%9D%B4%EC%8A%A4%EC%97%90%EC%84%9C%EB%A7%8C_%EC%84%9C%EB%B9%84%EC%8A%A4

Last update: **2021/05/03 07:24**