

DNS 3
BIND 9 (named) 3
DNSMASQ 3
 HOST 3
 DHCP 4

DNS

BIND 9 (named)

- <https://www.isc.org/>
- [underscore hostname - bad owner name\(check-names\)](#)
- [DNS forwarder\(resolver\)](#)

DNSMASQ

- wildcard domain

dnsmasq.conf

```
#address=/double-click.net/127.0.0.1
address=/ocp.example.com/192.168.0.151
address=/.ocp.example.com/192.168.0.151
```

- (upstream) DNS

dnsmasq.conf

```
# Change this line if you want dns to get its upstream servers from
# somewhere other than /etc/resolv.conf
resolv-file=/etc/dnsmasq-resolv.conf
```

```
[root@ocp ~]# cat /etc/dnsmasq-resolv.conf
nameserver 8.8.8.8
```

HOST

/etc/dnsmasq.d/dns.dns

```
domain-needed
bind-dynamic
bogus-priv
domain=ocp.example.com
interface=eth2
no-hosts

# host list file
```

```
addn-hosts=/etc/hosts.dnsmasq
expand-hosts

# wildcard address
address=/.apps.ocp.example.com/10.0.0.52
```

/etc/hosts.dnsmasq .

```
10.0.0.10 openshift-master-0
10.0.0.11 openshift-master-1
10.0.0.12 openshift-master-2
10.0.0.20 openshift-worker-0
10.0.0.21 openshift-worker-1
10.0.0.50 api
10.0.0.253 provisioner
```

DHCP

/etc/dnsmasq.d/dhcp.dns

```
domain-needed
bind-dynamic
bogus-priv
domain=ocp.example.com
dhcp-range=10.0.0.200,10.0.0.240

### PXE
enable-tftp
tftp-root=/var/lib/tftpboot
dhcp-boot=pxelinux/pxelinux.0

### dhcp option
# dhcp-option=3 ; 3=router
# dhcp-option=6 ; 6=dns-server
# dhcp-option=option:router
# dhcp-option=option:dns-server
# GW
dhcp-option=3,10.0.0.1
# DNS
dhcp-option=6,10.0.0.254

# upstream DNS
server=8.8.8.8
server=8.8.4.4
# upstream resolve
resolv-file=/etc/resolv.conf.upstream
```

```
# listen interface
interface=eth2

# DHCP MAC Address      hostname, IP      .
dhcp-host=00:50:56:86:25:d6,provisioner.ocp.example.com,10.0.0.253
dhcp-host=00:50:56:86:b1:1a,openshift-master-0.ocp.example.com,10.0.0.10
dhcp-host=00:50:56:86:ad:2a,openshift-master-1.ocp.example.com,10.0.0.11
dhcp-host=00:50:56:86:76:93,openshift-master-2.ocp.example.com,10.0.0.12
dhcp-host=00:50:56:86:12:86,openshift-worker-0.ocp.example.com,10.0.0.20
dhcp-host=00:50:56:86:22:0b,openshift-worker-1.ocp.example.com,10.0.0.21
```

```
/etc/resolv.conf.upstream      DNS      .
```

```
#      DNS
nameserver 192.168.0.1
```

From:
<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:
<https://atl.kr/dokuwiki/doku.php/dns?rev=1620185133>

Last update: **2021/05/05 03:25**

