

**DRBD** ..... 3

**DRBD** ..... 3

    DRBD ..... 3

    ..... 3

**DRBD** ..... 3

    Single-primary mode : : ..... 4

    Dual-primary mode : : ..... 4

    ..... 4

**DRBD** ..... 5

    ..... 5

    CentOS ..... 5

    ..... 5

**DRBD** ..... 6

    global ..... 7

    common ..... 7

    resource ..... 7

    ..... 8

    initial device synchronization : ..... 8

    Using truck based replication : ..... 8

    4 ..... 9

**DRBD** ..... 12



# DRBD

: <https://docs.linbit.com/docs/users-guide-9.0/>

## DRBD


## DRBD

DRBD ( , , ) . DRBD .

- 가 가
- 가 가
- ( ) 가

DRBD Linux , DRBD 가 DRBD DRBD I/O 가 가

DRBD Linux 가 가 가 . DRBD DRBD가 DRBD ext3 XFS 가




## DRBD

## Single-primary mode :

(ext3, ext4, XFS )  
DRBD 가 ( 가 )

## Dual-primary mode :

가 가  
GFS OCFS2가  
DRBD 가  
DRBD ( : 가

 DRBD-9.0 ( 가 ). DRBD-9.1  
2 가

DRBD 3 가 3 가

### A : Async

TCP 가 (failover)가  
가 DRBD A 가  
DRBD

### B : Semi-Async

( ) 가 (failover)

가 가 가

가

### C : Sync

가

( 가 )가 가

DRBD

가

C

가

## DRBD

SLES 가

(HAE)

DRBD가

. SLES

DRBD

YaST2

가

```
# yast -i drbd
```

```
# zypper install drbd
```

## CentOS

CentOS

5

DRBD 8 가

. DRBD 9

EPEL, ELRepo

. DRBD

yum(

가

).

```
# yum install drbd kmod-drbd
```

Ubuntu LTS

LINBIT

<https://launchpad.net/~linbit/+archive/ubuntu/linbit-drbd9-stack>

PPA

PPA

가

```
# apt-get install drbd-utils python-drbdmanage drbd-dkms
```

## DRBD

- DRBD

```
global {
    usage-count yes;
}
common {
    net {
        protocol C;
    }
}
```

- DRBD

```
resource r0 {
    on alice {
        device    /dev/drbd1;
        disk      /dev/sda7;
        address   10.1.1.31:7789;
        meta-disk internal;
    }
    on bob {
        device    /dev/drbd1;
        disk      /dev/sda7;
        address   10.1.1.32:7789;
        meta-disk internal;
    }
}
```

- DRBD

```
resource r0 {
    volume 0 {
        device    /dev/drbd1;
        disk      /dev/sda7;
        meta-disk internal;
    }
    volume 1 {
        device    /dev/drbd2;
        disk      /dev/sda8;
        meta-disk internal;
    }
}
```

```

on alice {
  address 10.1.1.31:7789;
}
on bob {
  address 10.1.1.32:7789;
}
}

```

### global

/etc/drbd.d/global\_common.conf

가

usage-count

DRBD

DRBD

DRBD

HTTP

usage-count no;

usage-count ask; DRBD

DRBD

( <http://usage.drbd.org> ).

### common

/etc/drbd.d/global\_common.conf

common

common net { protocol C; }

resource

가

### resource

/etc/drbd.d/resource.res

DRBD

on host

(

)

common

(

) DRBD

resource

```

resource r0 {
  device /dev/drbd1;
}

```

```
disk /dev/sda7;
meta-disk internal;
on alice {
    address 10.1.1.31:7789;
}
on bob {
    address 10.1.1.32:7789;
}
}
```

### initial device synchronization :

가

```
# drbdadm primary --force <resource>
```

### Using truck based replication :

가

```
# drbdadm new-current-uuid --clear-bitmap <resource>/<volume>
```

```
# drbdsetup new-current-uuid --clear-bitmap <minor>
```

```
dd if=/dev/zero of=/dev/sda7 bs=1M count=1024 conv=notrunc,fsync
        RAID1
        (file-copy
        1
        .)
```

가

```
# drbdadm new-current-uuid <resource>
```



-clear-bitmap

r0 0 2 1

```
V=r0/0
```

```
NODE_FROM=2
```

```
NODE_TO=1
```

```
drbdadm -- --force dump-md $V > /tmp/md_orig.txt
sed -e "s/node-id $NODE_FROM/node-id $NODE_TO/" \
    -e "s/^peer.$NODE_FROM. /peer-NEW /" \
    -e "s/^peer.$NODE_TO. /peer[$NODE_FROM] /" \
    -e "s/^peer-NEW /peer[$NODE_TO] /" \
    < /tmp/md_orig.txt > /tmp/md.txt
```

```
drbdmeta --force $(drbdadm sh-minor $V) v09 $(drbdadm sh-ll-dev $V) internal
restore-md /tmp/md.txt
```

```
# drbdadm up <resource>
```

가

4

4

```
resource r0 {
    device      /dev/drbd0;
    disk        /dev/vg/r0;
    meta-disk   internal;

    on store1 {
        address  10.1.10.1:7100;
        node-id  1;
    }
    on store2 {
        address  10.1.10.2:7100;
        node-id  2;
    }
    on store3 {
        address  10.1.10.3:7100;
```

```
node-id 3;
}
on store4 {
  address 10.1.10.4:7100;
  node-id 4;
}

# All connections involving store1
connection {
  host store1 port 7012;
  host store2 port 7021;
}
connection {
  host store1 port 7013;
  host store3 port 7031;
}
connection {
  host store1 port 7014;
  host store4 port 7041;
}

# All remaining connections involving store2
connection {
  host store2 port 7023;
  host store3 port 7032;
}
connection {
  host store2 port 7024;
  host store4 port 7042;
}

# All remaining connections involving store3
connection {
  host store3 port 7034;
  host store4 port 7043;
}

# store4 already done.
}
```

4 가 Full-mesh

1-2, 1-3, 1-4, 2-3, 2-4, 3-4

```
resource r0 {
  device /dev/drbd0;
  disk /dev/vg/r0;
```

```
meta-disk internal;

on store1 {
  address 10.1.10.1:7100;
  node-id 1;
}
on store2 {
  address 10.1.10.2:7100;
  node-id 2;
}
on store3 {
  address 10.1.10.3:7100;
  node-id 3;
}
on store4 {
  address 10.1.10.4:7100;
  node-id 4;
}

connection-mesh {
  hosts store1 store2 store3 store4;
}
}
```

NIC가

IP

```
resource r0 {
  ...

  # store1 has crossover links like 10.99.1x.y
  connection {
    host store1 address 10.99.12.1 port 7012;
    host store2 address 10.99.12.2 port 7021;
  }
  connection {
    host store1 address 10.99.13.1 port 7013;
    host store3 address 10.99.13.3 port 7031;
  }
  connection {
    host store1 address 10.99.14.1 port 7014;
    host store4 address 10.99.14.4 port 7041;
  }

  # store2 has crossover links like 10.99.2x.y
  connection {
    host store2 address 10.99.23.2 port 7023;
    host store3 address 10.99.23.3 port 7032;
  }
  connection {
```

```
host store2 address 10.99.24.2 port 7024;
host store4 address 10.99.24.4 port 7042;
}

# store3 has crossover links like 10.99.3x.y
connection {
  host store3 address 10.99.34.3 port 7034;
  host store4 address 10.99.34.4 port 7043;
}
}
```

## DRBD

DRBD

drbd-overview

```
nina# drbd-overview
0:r0/0 Connected(*) Seco(*)/Prim(nina) UpTo(*)/Disk(nono)
    /mnt ext3 1008M 18M 940M 2%
1:r1/0 Connected(*) Secondary(*) UpTo(*)/Disk(nono)
5:r2/0 Connected(*) Seco(*)/Prim(nini) UpTo(*)/Disk(nono)
6:r2/1 Connected(*) Seco(*)/Prim(nini) UpTo(*)/Disk(nono)
```

- r0 0 nina( ) Primary ext3 /mnt
- nono .(DRBD )
- UpToDate .
- r1 .
- r2 nini .

From: <https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link: [https://at1.kr/dokuwiki/doku.php/drbd\\_%EC%82%AC%EC%9A%A9%EC%9E%90\\_%EC%95%88%EB%82%B4%EC%84%9C?rev=1527676087](https://at1.kr/dokuwiki/doku.php/drbd_%EC%82%AC%EC%9A%A9%EC%9E%90_%EC%95%88%EB%82%B4%EC%84%9C?rev=1527676087)

Last update: 2018/05/30 10:28

