

find	3
	3
	3
0	3
	3
	3
	3
	3
	3
가	4
	4
100	()	4
	()	4
	4
가	4
가	4
	4
	4
	5
	5
	5
	5
root	SetUID, SetGID, StickyBit	5
	.rhosts	5
.bash_histroy	5
	()	5
	5
	5
	5
(action)	6
	6
	7

Last update: find_
2020/02/21 https://atl.kr/dokuwiki/doku.php/find_%EB%AA%85%EB%A0%B9%EC%96%B4_%EC%82%AC%EC%9A%A9%EB%B2%95
03:40 -

find

: find [] [] []

0

```
find / -empty -exec ls -l {} \\;
```

```
find / -uid 500 -exec ls -l {} \;
```

```
find / -user nestgoer -print
```

```
find /home -name *.html -exec ls -l {} \;
```

```
find ~nestgoer -name *.bak -exec rm -f {} \;
```

```
find / -size +100M -exec ls -lh {} \;
```

가

```
find / -perm 4755 -exec ls -l {} \;
```

```
find /home/nestgoer -mmin 5 -exec ls -l {} \;
```

```
5 5 , +5 5 ( ), -5 5 ( )  
100 ( )
```

```
find /home/nestgoer -atime -100 -exec ls -l {} \;
```

```
( )
```

```
find /home -anewer /home/nestgoer/begin -exec ls -l {} \;
```

```
find /home -newer /home/nestgoer/begin -exec ls -l {} \;
```

가

```
find /home -executable -print
```

가

```
find /home -executable \! -writable -print
```

```
find /dev -type b -exec ls -l {} \;
```

```
find /dev -type c -exec ls -l {} \;
```

```
find /etc -type d -print;
```

```
find /home/nestgoer -type f -exec ls -l {} \;
```

```
find /etc -type l -exec ls -l {} \;
```

root **SetUID, SetGID, StickyBit**

```
find / -user root -perm 4755 -exec ls -l {} \;
```

.rhosts

```
find / -name .rhosts -exec ls -l {} \;
```

.bash_histroy

```
find / -name .bash_history -exec ls -lh {} \;
```

```
( )
```

```
find / -nouser -o -nogroup -exec ls -l {} \;
```

```
find /home -type f -exec egrep -i "linux" /dev/null {} \;
```

- -empty :
- -uid n : n UID
- -gid n : n GID

- -group :
• -name : 가
• -newer :
• -used n : n
• -user uname : uname (UID 가)
• -amin n : n
• -anewer :
• -atime n : n*24
• -mmin n : n
• -mtime n : n*24
• -executable : 가
• -readable : 가
• -writable : 가
• -fstype type : (type)
• -nogroup :
• -nouser : (ID)가
• -path :
• -perm : 가
• -perm -mode :
• -regex :
• -size n[cwbkMG] : n . b
• -type : . b,c,d,p,f,l,s
n +n n , -n n , n , n

(action)

- -delete :
• -exec command ; command
• -exec command {} + : command
• -ls : 'ls - dils'
• -ok command ; : -exec command
• -print :
• -printf format : format

- () : ()
• ! expr : expr
• -not expr : ! expr (POSIX)
• expr1 expr2 : AND . expr1 expr2 . expr2 가
• expr1 -a expr2 : 'expr1 expr2'
• expr1 -and expr2 : 'expr1 expr2' (POSIX)
• expr1 -o expr2 : OR . expr1 expr2 . expr2 가
• expr1 -or expr2 : 'expr1 -o expr2'

- : <https://webdir.tistory.com/155>

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!



Permanent link:
https://atl.kr/dokuwiki/doku.php/find_%EB%AA%85%EB%A0%B9%EC%96%B4_%EC%82%AC%EC%9A%A9%EB%B2%95

Last update: **2020/02/21 03:40**