

find 3

..... 3

..... 3

0 3

..... 3

..... 3

..... 3

..... 3

..... 3

가 4

..... 4

100 () 4

() 4

..... 4

가 4

가 4

..... 4

..... 5

..... 5

..... 5

..... 5

..... 5

root SetUID, SetGID, StickyBit 5

.rhosts 5

.bash_histroy 5

() 5

..... 5

..... 6

(action) 6

..... 6

..... 7

find

find 가 가 가 .

```
: find [ ] [ ] [ ]
```

0

```
find / -empty -exec ls -l {} \;
```

```
find / -uid 500 -exec ls -l {} \;
```

```
find / -user nestgoer -print
```

'-print' ' -exec ls -l \;' ls -l .

```
find /home -name *.html -exec ls -l {} \;
```

```
find ~nestgoer -name *.bak -exec rm -f {} \;
```

'-exec' '-exec {} 가 .' .

```
find / -size +100M -exec ls -lh {} \;
```

가

```
find / -perm 4755 -exec ls -l {} \;
```

```
find /home/nestgoer -mmin 5 -exec ls -l {} \;
```

```
5 5 , +5 5 ( ), -5 5 (
)
100 ( )
```

```
find /home/nestgoer -atime -100 -exec ls -l {} \;
```

```
( )
```

```
find /home -anewer /home/nestgoer/begin -exec ls -l {} \;
```

```
find /home -newer /home/nestgoer/begin -exec ls -l {} \;
```

가

```
find /home -executable -print
```

가

```
find /home -executable \! -writable -print
```

```
find /dev -type b -exec ls -l {} \;
```

```
find /dev -type c -exec ls -l {} \;
```

```
find /etc -type d -print;
```

```
find /home/nestgoer -type f -exec ls -l {} \;
```

```
find /etc -type l -exec ls -l {} \;
```

root SetUID, SetGID, StickyBit

```
find / -user root -perm 4755 -exec ls -l {} \;
```

.rhosts

```
find / -name .rhosts -exec ls -l {} \;
```

.bash_histroy

```
find / -name .bash_history -exec ls -lh {} \;
```

```
( )
```

```
find / -nouser -o -nogroup -exec ls -l {} \;
```

```
find /home -type f -exec egrep -i "linux" /dev/null {} \;
```

- -empty :
 - -uid n : n UID
 - -gid n : n GID
 - -group :
 - -name : 가
 - -newer :
 - -used n : n
 - -user uname : uname (UID 가)
 - -amin n : n
 - -anewer :
 - -atime n : n*24
 - -mmin n : n
 - -mtime n : n*24
 - -executable : 가
 - -readable : 가
 - -writable : 가
 - -fstype type : (type)
 - -nogroup :
 - -nouser : (ID)가
 - -path :
 - -perm : 가
 - -perm -mode : 가
 - -regex :
 - -size n[cwbkMG] : n b
 - -type : . b,c,d,p,f,l,s
- n +n n , -n n , n n

(action)

- -delete :
 - -exec command ; : command
 - -exec command {} + : command
 - -ls : 'ls - dils'
 - -ok command ; ; -exec command
 - -print :
 - -printf format : format
- () : ()
 - ! expr : expr
 - -not expr : ! expr (POSIX)
 - expr1 expr2 : AND . expr1 expr2 가
 - expr1 -a expr2 : 'expr1 expr2'

- expr1 -and expr2 : 'expr1 expr2' (POSIX)
- expr1 -o expr2 : OR . expr1 expr2 가 .
- expr1 -or expr2 : 'expr1 -o expr2'

- : <https://webdir.tistory.com/155>

From:
<https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://at1.kr/dokuwiki/doku.php/find_%EB%AA%85%EB%A0%B9%EC%96%B4_%EC%82%AC%EC%9A%A9%EB%B2%95?rev=1582256382

Last update: 2020/02/21 03:39

