

**FloatIP(VIP) route Resource** ..... 3

..... 3

..... 3

..... 3



# FloatIP(VIP) route Resource

Cluster 가	VIP .	가	VIP .	가
		host	real IP	가

ocf:heartbeat:IPsrcaddr

- RHEL 7: resource-agents-4.1.1-46.el7 or later
- RHEL 8: resource-agents-4.1.1-44.el8 or later

- VIP : 192.168.0.130/24

```
[root@rhcs1 ~]# pcs resource create VirtualIP ocf:heartbeat:IPaddr2
ip=192.168.0.130 cidr_netmask=24 --group VIP
[root@rhcs1 ~]# pcs resource create SRC_IP ocf:heartbeat:IPsrcaddr
ipaddress=192.168.0.130 --group VIP
```

- <https://access.redhat.com/solutions/3459471>
- <https://access.redhat.com/solutions/3724391>
- <https://access.redhat.com/solutions/391453>
- <https://blog.naver.com/autowiz/221540062413>

From:  
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:  
[https://atl.kr/dokuwiki/doku.php/floatip\\_vip\\_route\\_resource](https://atl.kr/dokuwiki/doku.php/floatip_vip_route_resource)

Last update: 2020/11/27 10:49

