

Grub boot kernel argument 3

grubby 3

 3

Grub boot kernel argument

: RHEL7

grubby

```
#          가
# grubby --update-kernel=ALL --args="<NEW_PARAMETER>"

#          가          (          ""          )
# grubby --update-kernel=ALL --args="rd.lvm.lv=vg/lv1 rd.lvm.lv=vg/lv2"

#
# grubby --update-kernel=ALL --remove-args="<PARAMETER_TO_REMOVE>"

#
# grubby --update-kernel=/boot/vmlinuz-$(uname -r) --args="<NEW_PARAMETER>"
```

/etc/default/grub

```
GRUB_TERMINAL="serial"
GRUB_SERIAL_COMMAND="serial --speed=9600 --unit=0 --word=8 --parity=no --
stop=1"
```

GRUB configuration

```
# Legacy-BIOS System
# grub2-mkconfig -o /boot/grub2/grub.cfg

# UEFI-BIOS System
# grub2-mkconfig -o /boot/efi/EFI/redhat/grub.cfg
```

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/grub_boot_kernel_argument_%EC%84%A4%EC%A0%95?rev=1681454146

Last update: 2023/04/14 06:35

