

How to set root password in overcloud nodes? 3

..... 4

How to set root password in overcloud nodes?

Overcloud

root



3가

1. 가

2. root (overcloud-full.qcow2 root)
 libguestfs-tools 가 Director
 /home/stack/images/overcloud-full.qcow2 .

```
[root@redhat ~]# virt-customize -a overcloud-full.qcow2 --root-password
password:NEWPASSWORD
[ 0.0] Examining the guest ...
[ 5.6] Setting a random seed
[ 5.6] Setting the machine ID in /etc/machine-id
[ 5.6] Setting passwords
[ 6.5] Finishing off
[root@redhat ~]#
```

3. NodeUserData .

- NodeUserData
 - /usr/share/openstack-tripleo-heat-templates/firstboot/userdata_root_password.yaml
- .

```
resource_registry:
  OS::TripleO::NodeUserData: /usr/share/openstack-tripleo-heat-
  templates/firstboot/userdata_root_password.yaml

parameter_defaults:
  NodeRootPassword: 'MyPassword'
```

- . 1.

Last update:

2022/09/07 how_to_set_root_password_in_overcloud_nodes https://atl.kr/dokuwiki/doku.php/how_to_set_root_password_in_overcloud_nodes
05:21

- **OS::TripleO::NodeUserData**

- <https://access.redhat.com/solutions/4364591>

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/how_to_set_root_password_in_overcloud_nodes

Last update: **2022/09/07 05:21**

