

HW

..... 3


```
Bus: primary=16, secondary=18, subordinate=1b, sec-latency=0
I/O behind bridge: [disabled]
Memory behind bridge: 97700000-97afffff [size=4M]
Prefetchable memory behind bridge: 0000000092000000-00000000972fffff
[size=83M]
Secondary status: 66MHz- FastB2B- ParErr- DEVSEL=fast >TAbort-
<TAbort- <MAbort+ <SERR- <PERR-
BridgeCtl: Parity+ SERR+ NoISA- VGA- VGA16+ MAbort- >Reset- FastB2B-
PriDiscTmr- SecDiscTmr- DiscTmrStat- DiscTmrSERREn-
Capabilities: <access denied>
Kernel driver in use: pcieport
```

```
PCI Bridge
PCI 가 가 . 가
-t 가 tree . -tvvnnQ
```

```
$ lspci -s 16:01.0 -tvv
0000:16:01.0-[18-1b]----00.0-[19-1b]----03.0-[1a-1b]---+00.0 Intel
Corporation Ethernet Connection X722 for 1GbE
+00.1 Intel
Corporation Ethernet Connection X722 for 1GbE
+00.2 Intel
Corporation Ethernet Connection X722 for 1GbE
\00.3 Intel
Corporation Ethernet Connection X722 for 1GbE
```

From: <https://atl.kr/dokuwiki/> - AllThatLinux!
Permanent link: https://atl.kr/dokuwiki/doku.php/hw_%EC%9E%A5%EC%95%A0_%ED%99%95%EC%9D%B8
Last update: 2022/01/26 04:03

