

- Instance root password injection** ..... 3
- ..... 3
- Red Hat Enterprise Linux*** ..... 4
- ..... 4



# Instance root password injection

/ root . key pair  
root password

## Launch Instance



Details \*

You can customize your instance after it has launched using the options available here. "Customization Script" is analogous to "User Data" in other systems.

Source

### Load Customization Script from a file

Browse...

No file selected.

Flavor \*

### Customization Script (Modified)

Content size: 87 bytes of 16.00 KB

Networks

```
#cloud-config
ssh_pwauth: True
chpasswd:
  list: |
    root:<password>
    expire: False
```

Network Ports

Security Groups

Key Pair

Configuration

### Disk Partition

Server Groups

Automatic

Scheduler Hints

Configuration Drive

Metadata

Cancel

< Back

Next >

Launch Instance

(configuration)

```
#cloud-config
ssh_pwauth: True
chpasswd:
  list: |
    root:<password>
    cloud-user:<password>
  expire: False
```

<password>

- <https://techglimpse.com/nova-boot-instance-with-password/>

# Red Hat Enterprise Linux

RHEL

ssh

root login

가

가

.

```
#cloud-config
# vim:syntax=yaml
debug: True
ssh_pwauth: True
disable_root: false
chpasswd:
  list: |
    root:password
    cloud-user:password
  expire: false
runcmd:
- sed -i '.orig' -e 's/without-password/yes/' /etc/ssh/sshd_config
- sed -i -e '/^Port/s/^.*$/Port 4444/' /etc/ssh/sshd_config
- sed -i -e '/^PermitRootLogin/s/^.*$/PermitRootLogin no/'
/etc/ssh/sshd_config
- service sshd restart
```

- <https://cloudinit.readthedocs.io/en/latest/index.html>
- <https://access.redhat.com/discussions/499513>
- [https://access.redhat.com/documentation/en-us/red\\_hat\\_openstack\\_platform/16.0/html/instance\\_s\\_and\\_images\\_guide/ch-manage\\_instances#section-inject-admin-password](https://access.redhat.com/documentation/en-us/red_hat_openstack_platform/16.0/html/instance_s_and_images_guide/ch-manage_instances#section-inject-admin-password)
- [https://access.redhat.com/documentation/en-us/red\\_hat\\_enterprise\\_linux\\_atomic\\_host/7/html/installation\\_and\\_configuration\\_guide/setting\\_up\\_cloud\\_init](https://access.redhat.com/documentation/en-us/red_hat_enterprise_linux_atomic_host/7/html/installation_and_configuration_guide/setting_up_cloud_init)

From:

<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:

[https://atl.kr/dokuwiki/doku.php/instance\\_root\\_password\\_injection](https://atl.kr/dokuwiki/doku.php/instance_root_password_injection)Last update: **2023/07/20 15:39**