

<b>Instance root password injection .....</b>	<b>3</b>
.....	3



# Instance root password injection

/ root . key pair  
root password

## Launch Instance

Details \*

You can customize your instance after it has launched using the options available here. "Customization Script" is analogous to "User Data" in other systems.

Source [Load Customization Script from a file](#)

Flavor \*

Networks

Network Ports

Security Groups

Key Pair

Configuration

Server Groups

Scheduler Hints

Metadata

Browse... No file selected.

Customization Script (Modified)

Content size: 87 bytes of 16.00 KB

```
#cloud-config
ssh_pwauth: True
chpasswd:
  list: |
    root:<password>
  expire: False
```

Disk Partition

Automatic

Configuration Drive

[Cancel](#) [Back](#) [Next](#) [Launch Instance](#)

(configuration)

```
#cloud-config
ssh_pwauth: True
chpasswd:
  list: |
    root:<password>
    cloud-user:<password>
  expire: False
```

<password>

- <https://techglimpse.com/nova-boot-instance-with-password/>

From:  
<https://atl.kr/dokuwiki/> - AllThatLinux!



Permanent link:  
[https://atl.kr/dokuwiki/doku.php/instance\\_root\\_password\\_injection?rev=1631842479](https://atl.kr/dokuwiki/doku.php/instance_root_password_injection?rev=1631842479)

Last update: **2021/09/17 01:34**