

Instance root password injection 3
..... 3
Red Hat Enterprise Linux 4

Instance root password injection

/ root . key pair
root password

Launch Instance



Details *

You can customize your instance after it has launched using the options available here. "Customization Script" is analogous to "User Data" in other systems.

Source

Load Customization Script from a file

Browse...

No file selected.

Flavor *

Customization Script (Modified)

Content size: 87 bytes of 16.00 KB

```
#cloud-config
ssh_pwauth: True
chpasswd:
  list: |
    root:<password>
    expire: False
```

Networks

Network Ports

Security Groups

Key Pair

Configuration

Server Groups

Scheduler Hints

Metadata

Disk Partition

Automatic

Configuration Drive

Cancel

< Back

Next >

Launch Instance

(configuration)

```
#cloud-config
ssh_pwauth: True
chpasswd:
  list: |
    root:<password>
    cloud-user:<password>
  expire: False
```

<password>

- <https://techglimpse.com/nova-boot-instance-with-password/>

Red Hat Enterprise Linux

RHEL ssh password login 가 가 .

```
#cloud-config
# vim:syntax=yaml
debug: True
ssh_pwauth: True
disable_root: false
chpasswd:
  list: |
    root:password
    cloud-user:password
  expire: false
runcmd:
- sed -i'.orig' -e's/without-password/yes/' /etc/ssh/sshd_config
- service sshd restart
```

From:
<https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://at1.kr/dokuwiki/doku.php/instance_root_password_injection?rev=1640312114

Last update: 2021/12/24 02:15

