

**Ironic BIOS or UEFI** ..... 3



# Ironic BIOS or UEFI

```

Bare Metal :
              (uefi bios)
              .
              가      가      uefi      bios      , bare metal
properties      capabilities      .      bare metal
              .
              uefi      , capabilities      :

```

```

openstack baremetal node set <node-uuid> --property
capabilities='boot_mode:uefi'

```

```

,      bios      , capabilities      :

```

```

openstack baremetal node set <node-uuid> --property
capabilities='boot_mode:bios'

```

```

Ironic      Yoga      bios      uefi
. uefi      boot_mode 가      Compute      flavor      extra_spec      가
:

```

```

openstack flavor set ironic-test-3 --property capabilities:boot_mode="uefi"
openstack server create boot --flavor ironic-test-3 --image test-image
instance-1

```

```

capabilities가 extra_spec      , nova
(ComputeCapabilitiesFilter) properties/capabilities      boot_mode가
bare metal      .      .

```

```

Compute      uefi      bios      가
      .      flavor      boot_mode가
bare metal      boot_mode가      , nova
bios      uefi      .

```

UEFI

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

[https://atl.kr/dokuwiki/doku.php/ironic\\_bios\\_or\\_uefi](https://atl.kr/dokuwiki/doku.php/ironic_bios_or_uefi)

Last update: **2024/10/21 01:59**

