
iSCSI	3
<i>iSCSI Target_RHEL 6</i>	3
tgt-setup-lun	3
<i>iSCSI Target_RHEL 7</i>	7

iSCSI

iSCSI Target_RHEL 6

- * HOST OS : CentOS 6.6 64bit
- * GUEST OS : CentOS 6.6 64bit

tgt-setup-lun

```
tgt-setup-lun : target          target          가          Script          .
                  iSCSI Target          .
```

Step.1 iSCSI Target

```
[root@iscsi ~]# yum install scsi-target-utils.x86_64 -y
```

```
[root@iscsi ~]# rpm -qa | grep scsi-target-utils
scsi-target-utils-1.0.24-16.el6.x86_64
```

Step.2 iSCSI Target

```
[root@iscsi ~]# service tgtd start
[root@iscsi ~]# service tgtd status
[root@iscsi ~]# chkconfig tgtd on
```

Step.3 iSCSI Target

- * LVM . * tgt-setup-lun

```
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK1-LV_Disk1 -n
iSCSI_Target1
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK2-LV_Disk2 -n
iSCSI_Target2
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK3-LV_Disk3 -n
iSCSI_Target3
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK4-LV_Disk4 -n
iSCSI_Target4
```

* targets.conf

```
[root@iscsi ~]#tgt-admin --dump | grep -v default-driver > target.conf
[root@iscsi ~]#vim target.conf
<target iqn.2001-04.com.iscsi-iSCSI_Target3> // iqn
    backing-store /dev/mapper/VG_DISK3-LV_Disk3
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target1>
    backing-store /dev/mapper/VG_DISK1-LV_Disk1
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target4>
    backing-store /dev/mapper/VG_DISK4-LV_Disk4
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target2>
    backing-store /dev/mapper/VG_DISK2-LV_Disk2
</target>

[root@iscsi ~]#
```

* tgtd

```
[root@iscsi ~]# service tgtd restart
```

* Target

```
[root@iscsi ~]# tgt-admin -s
```

```
Target 1: iqn.2015-04.com.iscsi-iSCSI_Target1
System information:
  Driver: iscsi
  State: ready
I_T nexus information:
LUN information:
  LUN: 0
    Type: controller
    SCSI ID: IET      00010000
    SCSI SN: beaf10
    Size: 0 MB, Block size: 1
```

```
    Online: Yes
    Removable media: No
    Prevent removal: No
    Readonly: No
    Backing store type: null
    Backing store path: None
    Backing store flags:
LUN: 1
    Type: disk
    SCSI ID: IET      00010001
    SCSI SN: beaf11
    Size: 32216 MB, Block size: 512
    Online: Yes
    Removable media: No
    Prevent removal: No
    Readonly: No
    Backing store type: rdwr
    Backing store path: /dev/mapper/VG_DISK1-LV_Disk1
    Backing store flags:
Account information:
ACL information:
    ALL
Target 2: iqn.2015-04.com.iscsi-iSCSI_Target2
System information:
    Driver: iscsi
    State: ready
I_T nexus information:
LUN information:
    LUN: 0
        Type: controller
        SCSI ID: IET      00020000
        SCSI SN: beaf20
        Size: 0 MB, Block size: 1
        Online: Yes
        Removable media: No
        Prevent removal: No
        Readonly: No
        Backing store type: null
        Backing store path: None
        Backing store flags:
    LUN: 1
        Type: disk
        SCSI ID: IET      00020001
        SCSI SN: beaf21
        Size: 10737 MB, Block size: 512
        Online: Yes
        Removable media: No
        Prevent removal: No
        Readonly: No
        Backing store type: rdwr
        Backing store path: /dev/mapper/VG_DISK2-LV_Disk2
```

```
        Backing store flags:
Account information:
ACL information:
    ALL
Target 3: iqn.2015-04.com.iscsi-iSCSI_Target3
System information:
    Driver: iscsi
    State: ready
I_T nexus information:
LUN information:
    LUN: 0
        Type: controller
        SCSI ID: IET      00030000
        SCSI SN: beaf30
        Size: 0 MB, Block size: 1
        Online: Yes
        Removable media: No
        Prevent removal: No
        Readonly: No
        Backing store type: null
        Backing store path: None
        Backing store flags:
    LUN: 1
        Type: disk
        SCSI ID: IET      00030001
        SCSI SN: beaf31
        Size: 5377 MB, Block size: 512
        Online: Yes
        Removable media: No
        Prevent removal: No
        Readonly: No
        Backing store type: rdwr
        Backing store path: /dev/mapper/VG_DISK3-LV_Disk3
        Backing store flags:
Account information:
ACL information:
    ALL
Target 4: iqn.2015-04.com.iscsi-iSCSI_Target4
System information:
    Driver: iscsi
    State: ready
I_T nexus information:
LUN information:
    LUN: 0
        Type: controller
        SCSI ID: IET      00040000
        SCSI SN: beaf40
        Size: 0 MB, Block size: 1
        Online: Yes
        Removable media: No
        Prevent removal: No
```

```
    Readonly: No
    Backing store type: null
    Backing store path: None
    Backing store flags:
LUN: 1
    Type: disk
    SCSI ID: IET      00040001
    SCSI SN: beaf41
    Size: 5344 MB, Block size: 512
    Online: Yes
    Removable media: No
    Prevent removal: No
    Readonly: No
    Backing store type: rdwr
    Backing store path: /dev/mapper/VG_DISK4-LV_Disk4
    Backing store flags:
Account information:
ACL information:
    ALL
```

* target

```
tgt-admin --delete ALL // .
tgt-admin --delete tid=4 // 4 .
tgt-admin --delete iqn.2015-04.com // iqn.2015-04.com .
```

iSCSI Target_RHEL 7

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
<https://atl.kr/dokuwiki/doku.php/iscsi?rev=1430891591>

Last update: **2015/06/18 15:49**

