
iSCSI	3
<i>iSCSI Target_RHEL 6</i>	3
tgt-setup-lun	3
<i>iSCSI Target_RHEL 7</i>	7
targetcli	7

iSCSI

iSCSI Target_RHEL 6

* HOST OS : CentOS 6.6 64bit * GUEST OS : CentOS 6.6 64bit

tgt-setup-lun

```
tgt-setup-lun : target          target          가          Script          .  
                  iSCSI Target
```

Step.1 iSCSI Target

```
[root@iscsi ~]# yum install scsi-target-utils.x86_64 -y
```

```
[root@iscsi ~]# rpm -qa | grep scsi-target-utils  
scsi-target-utils-1.0.24-16.el6.x86_64
```

Step.2 iSCSI Target

```
[root@iscsi ~]# service tgtd start  
[root@iscsi ~]# service tgtd status  
[root@iscsi ~]# chkconfig tgtd on
```

Step.3 iSCSI Target

* LVM . * tgt-setup-lun

```
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK1-LV_Disk1 -n  
iSCSI_Target1  
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK2-LV_Disk2 -n  
iSCSI_Target2  
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK3-LV_Disk3 -n  
iSCSI_Target3  
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK4-LV_Disk4 -n  
iSCSI_Target4
```

* targets.conf

```
[root@iscsi ~]#tgt-admin --dump | grep -v default-driver > target.conf
[root@iscsi ~]#vim target.conf
<target iqn.2001-04.com.iscsi-iSCSI_Target3> // iqn
    backing-store /dev/mapper/VG_DISK3-LV_Disk3
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target1>
    backing-store /dev/mapper/VG_DISK1-LV_Disk1
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target4>
    backing-store /dev/mapper/VG_DISK4-LV_Disk4
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target2>
    backing-store /dev/mapper/VG_DISK2-LV_Disk2
</target>

[root@iscsi ~]#
```

* tgd

```
[root@iscsi ~]# service tgd restart
```

* Target

```
[root@iscsi ~]# tgt-admin -s
```

```
Target 1: iqn.2015-04.com.iscsi-iSCSI_Target1
System information:
  Driver: iscsi
  State: ready
I_T nexus information:
LUN information:
  LUN: 0
    Type: controller
    SCSI ID: IET      00010000
    SCSI SN: beaf10
    Size: 0 MB, Block size: 1
    Online: Yes
    Removable media: No
    Prevent removal: No
```

```
    Readonly: No
    Backing store type: null
    Backing store path: None
    Backing store flags:
LUN: 1
    Type: disk
    SCSI ID: IET      00010001
    SCSI SN: beaf11
    Size: 32216 MB, Block size: 512
    Online: Yes
    Removable media: No
    Prevent removal: No
    Readonly: No
    Backing store type: rdwr
    Backing store path: /dev/mapper/VG_DISK1-LV_Disk1
    Backing store flags:
Account information:
ACL information:
    ALL
Target 2: iqn.2015-04.com.iscsi-iSCSI_Target2
System information:
    Driver: iscsi
    State: ready
I_T nexus information:
LUN information:
    LUN: 0
        Type: controller
        SCSI ID: IET      00020000
        SCSI SN: beaf20
        Size: 0 MB, Block size: 1
        Online: Yes
        Removable media: No
        Prevent removal: No
        Readonly: No
        Backing store type: null
        Backing store path: None
        Backing store flags:
    LUN: 1
        Type: disk
        SCSI ID: IET      00020001
        SCSI SN: beaf21
        Size: 10737 MB, Block size: 512
        Online: Yes
        Removable media: No
        Prevent removal: No
        Readonly: No
        Backing store type: rdwr
        Backing store path: /dev/mapper/VG_DISK2-LV_Disk2
        Backing store flags:
Account information:
ACL information:
```

ALL

Target 3: iqn.2015-04.com.iscsi-iSCSI_Target3

System information:

Driver: iscsi

State: ready

I_T nexus information:

LUN information:

LUN: 0

Type: controller

SCSI ID: IET 00030000

SCSI SN: beaf30

Size: 0 MB, Block size: 1

Online: Yes

Removable media: No

Prevent removal: No

Readonly: No

Backing store type: null

Backing store path: None

Backing store flags:

LUN: 1

Type: disk

SCSI ID: IET 00030001

SCSI SN: beaf31

Size: 5377 MB, Block size: 512

Online: Yes

Removable media: No

Prevent removal: No

Readonly: No

Backing store type: rdwr

Backing store path: /dev/mapper/VG_DISK3-LV_Disk3

Backing store flags:

Account information:

ACL information:

ALL

Target 4: iqn.2015-04.com.iscsi-iSCSI_Target4

System information:

Driver: iscsi

State: ready

I_T nexus information:

LUN information:

LUN: 0

Type: controller

SCSI ID: IET 00040000

SCSI SN: beaf40

Size: 0 MB, Block size: 1

Online: Yes

Removable media: No

Prevent removal: No

Readonly: No

Backing store type: null

Backing store path: None

```
    Backing store flags:
LUN: 1
    Type: disk
    SCSI ID: IET      00040001
    SCSI SN: beaf41
    Size: 5344 MB, Block size: 512
    Online: Yes
    Removable media: No
    Prevent removal: No
    Readonly: No
    Backing store type: rdwr
    Backing store path: /dev/mapper/VG_DISK4-LV_Disk4
    Backing store flags:
Account information:
ACL information:
    ALL
```

* target

```
tgt-admin --delete ALL // .
tgt-admin --delete tid=4 // 4 .
tgt-admin --delete iqn.2015-04.com // iqn.2015-04.com .
```

iSCSI Target_RHEL 7

* HOST OS : CentOS Linux release 7 * GUEST OS : CentOS Linux release 7

targetcli

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
<https://atl.kr/dokuwiki/doku.php/iscsi?rev=1430891723>

Last update: **2015/06/18 15:49**

