

iSCSI	3
<i>iSCSI Target_RHEL 6</i>	3
tgt-setup-lun	3
<i>iSCSI Target_RHEL 7</i>	7
targetcli	7

: <https://access.redhat.com/solutions/894163>

iSCSI

iSCSI Target_RHEL 6

* HOST OS : CentOS 6.6 64bit * GUEST OS : CentOS 6.6 64bit

tgt-setup-lun

tgt-setup-lun : target target 가 Script .
iSCSI Target .

Step.1 iSCSI Target

```
[root@iscsi ~]# yum install scsi-target-utils.x86_64 -y
```

```
[root@iscsi ~]# rpm -qa | grep scsi-target-utils
scsi-target-utils-1.0.24-16.el6.x86_64
```

Step.2 iSCSI Target

```
[root@iscsi ~]# service tgtd start
[root@iscsi ~]# service tgtd status
[root@iscsi ~]# chkconfig tgtd on
```

Step.3 iSCSI Target

* LVM . * tgt-setup-lun

```
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK1-LV_Disk1 -n
iSCSI_Target1
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK2-LV_Disk2 -n
iSCSI_Target2
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK3-LV_Disk3 -n
iSCSI_Target3
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK4-LV_Disk4 -n
iSCSI_Target4
```

* targets.conf

```
[root@iscsi ~]#tgt-admin --dump | grep -v default-driver > target.conf
[root@iscsi ~]#vim target.conf
<target iqn.2001-04.com.iscsi-iSCSI_Target3> // iqn
    backing-store /dev/mapper/VG_DISK3-LV_Disk3
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target1>
    backing-store /dev/mapper/VG_DISK1-LV_Disk1
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target4>
    backing-store /dev/mapper/VG_DISK4-LV_Disk4
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target2>
    backing-store /dev/mapper/VG_DISK2-LV_Disk2
</target>

[root@iscsi ~]#
```

* tgtd

```
[root@iscsi ~]# service tgtd restart
```

* Target

```
[root@iscsi ~]# tgt-admin -s
```

```
Target 1: iqn.2015-04.com.iscsi-iSCSI_Target1
System information:
    Driver: iscsi
    State: ready
I_T nexus information:
LUN information:
    LUN: 0
        Type: controller
        SCSI ID: IET      00010000
        SCSI SN: beaf10
        Size: 0 MB, Block size: 1
```

```
    Online: Yes
    Removable media: No
    Prevent removal: No
    Readonly: No
    Backing store type: null
    Backing store path: None
    Backing store flags:
LUN: 1
    Type: disk
    SCSI ID: IET      00010001
    SCSI SN: beaf11
    Size: 32216 MB, Block size: 512
    Online: Yes
    Removable media: No
    Prevent removal: No
    Readonly: No
    Backing store type: rdwr
    Backing store path: /dev/mapper/VG_DISK1-LV_Disk1
    Backing store flags:
Account information:
ACL information:
    ALL
Target 2: iqn.2015-04.com.iscsi-iSCSI_Target2
System information:
    Driver: iscsi
    State: ready
I_T nexus information:
LUN information:
    LUN: 0
        Type: controller
        SCSI ID: IET      00020000
        SCSI SN: beaf20
        Size: 0 MB, Block size: 1
        Online: Yes
        Removable media: No
        Prevent removal: No
        Readonly: No
        Backing store type: null
        Backing store path: None
        Backing store flags:
    LUN: 1
        Type: disk
        SCSI ID: IET      00020001
        SCSI SN: beaf21
        Size: 10737 MB, Block size: 512
        Online: Yes
        Removable media: No
        Prevent removal: No
        Readonly: No
        Backing store type: rdwr
        Backing store path: /dev/mapper/VG_DISK2-LV_Disk2
```

```
        Backing store flags:
Account information:
ACL information:
    ALL
Target 3: iqn.2015-04.com.iscsi-iSCSI_Target3
System information:
    Driver: iscsi
    State: ready
I_T nexus information:
LUN information:
    LUN: 0
        Type: controller
        SCSI ID: IET      00030000
        SCSI SN: beaf30
        Size: 0 MB, Block size: 1
        Online: Yes
        Removable media: No
        Prevent removal: No
        Readonly: No
        Backing store type: null
        Backing store path: None
        Backing store flags:
    LUN: 1
        Type: disk
        SCSI ID: IET      00030001
        SCSI SN: beaf31
        Size: 5377 MB, Block size: 512
        Online: Yes
        Removable media: No
        Prevent removal: No
        Readonly: No
        Backing store type: rdwr
        Backing store path: /dev/mapper/VG_DISK3-LV_Disk3
        Backing store flags:
Account information:
ACL information:
    ALL
Target 4: iqn.2015-04.com.iscsi-iSCSI_Target4
System information:
    Driver: iscsi
    State: ready
I_T nexus information:
LUN information:
    LUN: 0
        Type: controller
        SCSI ID: IET      00040000
        SCSI SN: beaf40
        Size: 0 MB, Block size: 1
        Online: Yes
        Removable media: No
        Prevent removal: No
```

```

        Readonly: No
        Backing store type: null
        Backing store path: None
        Backing store flags:
LUN: 1
    Type: disk
    SCSI ID: IET      00040001
    SCSI SN: beaf41
    Size: 5344 MB, Block size: 512
    Online: Yes
    Removable media: No
    Prevent removal: No
    Readonly: No
    Backing store type: rdwr
    Backing store path: /dev/mapper/VG_DISK4-LV_Disk4
    Backing store flags:
Account information:
ACL information:
    ALL

```

* target

```

tgt-admin --delete ALL // .
tgt-admin --delete tid=4 // 4 .
tgt-admin --delete iqn.2015-04.com // iqn.2015-04.com .

```

iSCSI Target_RHEL 7

* HOST OS : CentOS Linux release 7 * GUEST OS : CentOS Linux release 7

targetcli

targetcli

targetcli

Step1. Install and run targetcli

LVM

```
[root@server1 ~]# fdisk -l | grep Disk
```

```

Disk /dev/sda: 32.2 GB, 32212254720 bytes, 62914560 sectors
Disk /dev/sdb: 53.7 GB, 53687091200 bytes, 104857600 sectors // ISCSI
가
Disk /dev/mapper/centos-swap: 2164 MB, 2164260864 bytes, 4227072 sectors
Disk /dev/mapper/centos-root: 29.5 GB, 29519511552 bytes, 57655296 sectors

```

```

[root@server1 ~]# vgs
  VG                #PV #LV #SN Attr   VSize   VFree
  VG_iscsi_Disk1    1   1   0 wz--n- 1020.00m 0
  VG_iscsi_Disk2    1   1   0 wz--n-  10.00g 0
  centos            1   2   0 wz--n-  29.51g 0
[root@server1 ~]# lvs
  LV                VG                Attr      LSize   Pool Origin Data%  Move
Log Cpy%Sync Convert
  lv_iscsi_Disk1    VG_iscsi_Disk1  -wi-a----- 1020.00m
  lv_iscsi_Disk2    VG_iscsi_Disk2  -wi-a-----  10.00g
  root              centos          -wi-ao----   27.49g
  swap              centos          -wi-ao----    2.02g

```

targetcli :

```
# yum install targetcli
```

```
# targetcli --version
/usr/bin/targetcli version 2.1.fb37
```

* target service :

```
# systemctl start target
```

targetcli

```

[root@server1 ~]# targetcli
targetcli shell version 2.1.fb37
Copyright 2011-2013 by Datera, Inc and others.
For help on commands, type 'help'.

```

```
/> ls
```

```
o- /
```

```

.....
..... [....]
o- backstores
.....
..... [....]
| o- block
.....
..... [Storage Objects: 0]

```

```
| o- fileio
.....
..... [Storage Objects: 0]
| o- pscsi
.....
..... [Storage Objects: 0]
| o- ramdisk
.....
..... [Storage Objects: 0]
o- iscsi
.....
..... [Targets: 0]
o- loopback
.....
..... [Targets: 0]
/>
```

backstores

From:

<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:

<https://atl.kr/dokuwiki/doku.php/iscsi?rev=1453711353>

Last update: **2016/01/25 08:42**

