

**iSCSI Target** ..... 3  
***tgt-setup-lun*** ..... 3



# iSCSI Target

\* HOST OS : CentOS 6.6 64bit

\* GUEST OS : CentOS 6.6 64bit

## tgt-setup-lun

```

tgt-setup-lun : target          target          가          Script
                  iSCSI Target

```

### Step.1 iSCSI Target

```
[root@iscsi ~]# yum install scsi-target-utils.x86_64 -y
```

```
[root@iscsi ~]# rpm -qa | grep scsi-target-utils
scsi-target-utils-1.0.24-16.el6.x86_64
```

### Step.2 iSCSI Target

```
[root@iscsi ~]# service tgtd start
[root@iscsi ~]# service tgtd status
[root@iscsi ~]# chkconfig tgtd on
```

### Step.3 iSCSI Target

```
*          LVM          . * tgt-setup-lun
```

```
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK1-LV_Disk1 -n
iSCSI_Target1
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK2-LV_Disk2 -n
iSCSI_Target2
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK3-LV_Disk3 -n
iSCSI_Target3
[root@iscsi ~]# tgt-setup-lun -d /dev/mapper/VG_DISK4-LV_Disk4 -n
iSCSI_Target4
```

```
*          targets.conf
```

```
[root@iscsi ~]#tgt-admin --dump | grep -v default-driver > target.conf
[root@iscsi ~]#vim target.conf
<target iqn.2001-04.com.iscsi-iSCSI_Target3> // iqn
    backing-store /dev/mapper/VG_DISK3-LV_Disk3
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target1>
    backing-store /dev/mapper/VG_DISK1-LV_Disk1
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target4>
    backing-store /dev/mapper/VG_DISK4-LV_Disk4
</target>

<target iqn.2001-04.com.iscsi-iSCSI_Target2>
    backing-store /dev/mapper/VG_DISK2-LV_Disk2
</target>

[root@iscsi ~]#
```

From:  
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:  
[https://atl.kr/dokuwiki/doku.php/iscsi\\_target?rev=1428891301](https://atl.kr/dokuwiki/doku.php/iscsi_target?rev=1428891301)

Last update: **2015/06/18 15:49**

