

JBoss EAP 6.x Access log 3
Web Application 3
Engine Global 4
..... 5

JBoss EAP 6.x Access log

JBoss EAP 6.x Access log

Access log

2가 가 .

Web Application

JBoss EAP

Access log

. WEB-

INF/jboss-web.xml

AccessLogValve

.

```

<jboss-web>
  <valve>
    <class-name>org.apache.catalina.valves.AccessLogValve</class-name>
    <param>
      <param-name>prefix</param-name>
      <param-value>myapp_access_log.</param-value>
    </param>
    <param>
      <param-name>suffix</param-name>
      <param-value>.log</param-value>
    </param>
    <param>
      <param-name>fileDateFormat</param-name>
      <!-- You can use pattern letters defined in SimpleDateFormat.
           This fileDateFormat setting affects to log rotation cycle
      -->
      <!-- default setting: daily -->
      <param-value>yyyy-MM-dd</param-value>
      <!-- hourly
      <param-value>yyyy-MM-dd.HH</param-value>
      -->
    </param>
    <param>
      <param-name>pattern</param-name>
      <!-- You can use constant text or replacement strings defined in
           http://docs.jboss.org/jbossweb/7.0.x/config/valve.html to
pattern tokens.
      -->
      <!-- default setting: common (%h %l %u %t "%r" %s %b) -->
      <param-value>common</param-value>
      <!-- combined (%h %l %u %t "%r" %s %b "%{Referer}i" "%{User-
Agent}i")
      <param-value>combined</param-value>
      -->
      <!-- combined + response time
      <param-value>%h %l %u %t %r %s %b %{Referer}i %{User-Agent}i
%T</param-value>

```

```
-->
<!-- combined + Session ID + Response time
<param-value>%h %l %u %t %r %s %b %{Referer}i %{User-Agent}i %S
%T</param-value>
-->
</param>
<param>
  <param-name>directory</param-name>
  <param-value>${jboss.server.log.dir}</param-value>
</param>
<param>
  <param-name>resolveHosts</param-name>
  <param-value>>false</param-value>
</param>
</valve>
</jboss-web>
```

Engine Global

Access log

standalone.xml domain.xml <virtual-server> <access-log> 가 .

```
<access-log pattern='%h %l %u %t %r %s %b %{Referer}i %{User-Agent}i %S
%T' />
```

```
<subsystem xmlns="urn:jboss:domain:web:1.2" default-virtual-
server="default-host" native="false">
  <connector name="http" protocol="HTTP/1.1" scheme="http" socket-
binding="http"/>
  <virtual-server name="default-host" enable-welcome-root="true">
    <alias name="localhost"/>
    <alias name="example.com"/>
    <access-log pattern='%h %l %u %t %r %s %b %{Referer}i
%{User-Agent}i %S %T' prefix="access_log_"/>
  </virtual-server>
</subsystem>
```

CLI 가 .

```
/subsystem=web/virtual-server=default-host/configuration=access-log:add
/subsystem=web/virtual-server=default-host/configuration=access-log:write-
attribute(name="pattern",value="%h %l %u %t \"%r\" %s %b %S %T")
```

- <https://access.redhat.com/solutions/185383>

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/jboss_eap_6.x_access_log_%EC%84%A4%EC%A0%95

Last update: **2017/07/12 08:51**

