

**JBoss EAP 6.x Bind Address** ..... 3  
**NIC** ..... 3  
**Cluster(JGroups)**                    **bind address** ..... 3  
..... 4



— 2015/07/29 11:05

# JBoss EAP 6.x Bind Address

bind address

2가 가

## 1. cli

```
$JBOSS_HOME/bin/standalone.sh -b=0.0.0.0
#
$JBOSS_HOME/bin/standalone.sh -bmanagement=192.168.100.10
```

## 2. xml

```
<interfaces>
  <interface name="management">
    <inet-address value="{jboss.bind.address.management:127.0.0.1}"/>
  </interface>
  <interface name="public">
    <inet-address value="{jboss.bind.address:127.0.0.1}"/>
  </interface>
</interfaces>
```

## NIC

IP Address가

NIC

xml

```
<interfaces>
  <interface name="management">
    <nic name="eth1"/>
  </interface>
  <interface name="public">
    <nic name="eth0"/>
  </interface>
</interfaces>
```

## Cluster(JGroups)

## bind address

bind address가 0.0.0.0  
2가 가

bind address any(0.0.0.0)

가

- 1. bind address real-IP
  - 2. bind address 0.0.0.0 cluster jgroups address real-ip
- . 2 .

```
$JBOSS_HOME/bin/standalone.sh -b 0.0.0.0 -Djgroups.bind_addr=192.168.1.100
```

, jgroups.bind\_addr bind address 가

- <https://access.redhat.com/solutions/41876>

From: <https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link: [https://atl.kr/dokuwiki/doku.php/jboss\\_eap\\_6.x\\_bind\\_address\\_%EC%84%A4%EC%A0%95](https://atl.kr/dokuwiki/doku.php/jboss_eap_6.x_bind_address_%EC%84%A4%EC%A0%95)

Last update: 2017/10/27 02:43

