

JBoss EAP 6.x Bind Address 3
NIC 3
Cluster(JGroups) **bind address** 3
..... 4

— 2015/07/29 11:05

JBoss EAP 6.x Bind Address

bind address

2가 가

1. cli

```
$JBOSS_HOME/bin/standalone.sh -b=0.0.0.0
#
$JBOSS_HOME/bin/standalone.sh -bmanagement=192.168.100.10
```

2. xml

```
<interfaces>
  <interface name="management">
    <inet-address value="{jboss.bind.address.management:127.0.0.1}"/>
  </interface>
  <interface name="public">
    <inet-address value="{jboss.bind.address:127.0.0.1}"/>
  </interface>
</interfaces>
```

NIC

IP Address가

NIC

xml

```
<interfaces>
  <interface name="management">
    <nic name="eth1"/>
  </interface>
  <interface name="public">
    <nic name="eth0"/>
  </interface>
</interfaces>
```

Cluster(JGroups)

bind address

bind address가 0.0.0.0
2가 가

bind address any(0.0.0.0)

가

1. bind address real-IP
 2. bind address 0.0.0.0 cluster jgroups address real-ip
- . 2 .

```
$JBOSS_HOME/bin/standalone.sh -b 0.0.0.0 -Djgroups.bind_addr=192.168.1.100
```

, jgroups.bind_addr bind address 가

- <https://access.redhat.com/solutions/41876>

From: <https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link: https://atl.kr/dokuwiki/doku.php/jboss_eap_6.x_bind_address_%EC%84%A4%EC%A0%95

Last update: 2017/10/27 02:43

