

<b>JBoss EAP 6.x Bind Address</b>	.....	3
<b><i>NIC</i></b>	.....	3



# JBoss EAP 6.x Bind Address

bind address

2가 가

## 1. cli

```
$JBOSS_HOME/bin/standalone.sh -b=0.0.0.0  
  
#  
$JBOSS_HOME/bin/standalone.sh -bmanagement=192.168.100.10
```

## 2. xml

```
<interfaces>  
  <interface name="management">  
    <inet-address value="{jboss.bind.address.management:127.0.0.1}"/>  
  </interface>  
  <interface name="public">  
    <inet-address value="{jboss.bind.address:127.0.0.1}"/>  
  </interface>  
</interfaces>
```

## NIC

IP Address가

NIC

xml

```
<interfaces>  
  <interface name="management">  
    <nic name="eth1"/>  
  </interface>  
  <interface name="public">  
    <nic name="eth0"/>  
  </interface>  
</interfaces>
```

From:

<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:

[https://atl.kr/dokuwiki/doku.php/jboss\\_eap\\_6.x\\_bind\\_address\\_%EC%84%A4%EC%A0%95?rev=1437359339](https://atl.kr/dokuwiki/doku.php/jboss_eap_6.x_bind_address_%EC%84%A4%EC%A0%95?rev=1437359339)

Last update: 2015/07/20 02:28

