

JBoss EAP 6.x Bind Address	3
NIC	3
Cluster(JGroups)	bind address	3

JBoss EAP 6.x Bind Address

bind address

2가 가

1. cli

```
$JBOSS_HOME/bin/standalone.sh -b=0.0.0.0

#
$JBOSS_HOME/bin/standalone.sh -bmanagement=192.168.100.10
```

2. xml

```
<interfaces>
  <interface name="management">
    <inet-address value="{jboss.bind.address.management:127.0.0.1}"/>
  </interface>
  <interface name="public">
    <inet-address value="{jboss.bind.address:127.0.0.1}"/>
  </interface>
</interfaces>
```

NIC

IP Address가

NIC

xml

```
<interfaces>
  <interface name="management">
    <nic name="eth1"/>
  </interface>
  <interface name="public">
    <nic name="eth0"/>
  </interface>
</interfaces>
```

Cluster(JGroups)

bind address

bind address any(0.0.0.0)

bind address가 0.0.0.0
2가 가

가

1. bind address real-IP

2. bind address 0.0.0.0 cluster jgroups address real-ip
. 2 .

```
$JBOSS_HOME/bin/standalone.sh -b 0.0.0.0 -Djgroups.bind_addr=192.168.1.100
```

, jgroups.bind_addr bind address 가
.

From:
<https://at1.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://at1.kr/dokuwiki/doku.php/jboss_eap_6.x_bind_address_%EC%84%A4%EC%A0%95?rev=1437359577

Last update: 2015/07/20 02:32

