

JBoss EAP 6.x JSP Hot Deploy 3
..... 3
..... 3

JBoss EAP 6.x JSP Hot Deploy

- JSP reloadable="true"
- development mode

: <https://access.redhat.com/solutions/334963>

- JSP 가
- JSP , ?
- NetBeans JSP ?
- JBoss (JSP) ?

- EAP 6 JSP development check-interval
- Jasper work JSP 가 (work 가
- touch JSP 가
- web development True JSP가

```
<subsystem xmlns="urn:jboss:domain:web:1.1" default-virtual-server="default-host" native="false">
  <configuration>
    <jsp-configuration development="true"/>
  </configuration>
</subsystem>
```

- CLI

```
[standalone @ localhost : 9999 /] / subsystem = web / configuration = jsp-configuration : write-attribute (name = development, value = true)
{
  "outcome"=> "success",
  "response-headers"=> {
    " operation-requires-reload "=> true,
    "process-state "=>"reload-required "
  }
}
```

```
[standalone @ localhost : 9999 /] / subsystem = web / configuration = jsp-configuration : read-resource (recursive = true)
{
  "outcome"=> "success",
  "result"=> {
    "check-interval"=> 0,
    "development"=> "true",
    "disabled"=> false,
    "display-source-fragment"=> true,
    "dump-smap"=> false,
    "error-on-use-bean-invalid-class -attribute "=> false,
    "generate-strings-as-char-arrays "=> false,
    "java-encoding "=>"UTF8 ",
    "keep-generated "=> true,
    "mapped-file "=> true ,
    "modification-test-interval"=> 4,
    "recompile-on-fail"=> false,
    "scratch-dir"=> undefined,
    "smap"=> true,
    "source-vm"=> "1.5"
    "tag-pooling"=> true,
    "target-vm"=> "1.5",
    "trim-spaces"=> false,
    "x-powered-by"=> true
  }
}
```

- 가 () check-interval
JSP

```
<subsystem xmlns = "urn : jboss : domain : web : 1.1" default-virtual-
server = "default-host" native = "false">
  <configuration>
    <jsp-configuration check-interval = "600"/>
  </ configuration>
```

From: <https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link: https://atl.kr/dokuwiki/doku.php/jboss_eap_6.x_jsp_hot_deploy_%EC%84%A4%EC%A0%95_%EB%B0%A9%EB%B2%95

Last update: 2016/03/17 01:37

