

<b>JBoss EAP 6.x JSP Hot Deploy</b>	.....	3
.....	.....	3
.....	.....	3

Last  
update: jboss\_eap\_6.x\_jsp\_hot\_deploy\_ [https://atl.kr/dokuwiki/doku.php/jboss\\_eap\\_6.x\\_jsp\\_hot\\_deploy\\_%EC%84%A4%EC%A0%95\\_%EB%B0%A9%EB%B2%95](https://atl.kr/dokuwiki/doku.php/jboss_eap_6.x_jsp_hot_deploy_%EC%84%A4%EC%A0%95_%EB%B0%A9%EB%B2%95)  
2016/03/17 -  
01:37

---

# JBoss EAP 6.x JSP Hot Deploy

- reloadable="true"
  - development mode

: <https://access.redhat.com/solutions/334963>



- EAP 6 JSP development check-interval
  - Jasper work JSP 가 . (work JSP 가  
.)
  - touch JSP 가
  - web development True JSP 가

```
<subsystem xmlns="urn:jboss:domain:web:1.1" default-virtual-server="default-host" native="false">
    <configuration>
        <jsp-configuration development="true"/>
    </configuration>
```

- CLI

```
[standalone @ localhost : 9999 /] / subsystem = web / configuration = jsp-  
configuration : write-attribute (name = development, value = true)  
{  
    "outcome"=> "success",  
    "response-headers"=> {  
        "operation-requires-reload"=> true,  
        "process-state"=>"reload-required"  
    }  
}
```

•

```
[standalone @ localhost : 9999 /] / subsystem = web / configuration = jsp-configuration : read-resource (recursive = true)
{
    "outcome"=> "success",
    "result"=> {
        "check-interval"=> 0,
        "development"=> "true",
        "disabled"=> false,
        "display-source-fragment"=> true,
        "dump-smap"=> false,
        "error-on-use-bean-invalid-class -attribute"=> false,
        "generate-strings-as-char-arrays"=> false,
        "java-encoding"=>"UTF8",
        "keep-generated"=> true,
        "mapped-file"=> true ,
        "modification-test-interval"=> 4,
        "recompile-on-fail"=> false,
        "scratch-dir"=> undefined,
        "smap"=> true,
        "source-vm"=> "1.5"
        "tag-pooling"=> true,
        "target-vm"=> "1.5",
        "trim-spaces"=> false,
        "x-powered-by"=> true
    }
}
```

•

가

( )

check-interval

JSP

```
<subsystem xmlns = "urn : jboss : domain : web : 1.1" default-virtual-server = "default-host" native = "false">
    <configuration>
        <jsp-configuration check-interval = "600"/>
    </ configuration>
```

