

**JBoss EAP 6.x TCP clustering** ..... 3



# JBoss EAP 6.x TCP clustering

```
initial_hosts      . num_initial_members
+ 1                .
```

```
<stack name="tcp">
  <transport type="TCP" socket-binding="jgroups-tcp"/>
  <protocol type="TCPPING">
    <property name="initial_hosts">
      HostA[7600],HostB[7600]
    </property>
    <property name="port_range">
      0
    </property>
    <property name="timeout">
      3000
    </property>
    <property name="num_initial_members">
      3
    </property>
  </protocol>
  <protocol type="MERGE2"/>
  <protocol type="FD_SOCK" socket-binding="jgroups-tcp-fd"/>
  <protocol type="FD"/>
  <protocol type="VERIFY_SUSPECT"/>
  <protocol type="BARRIER"/>
  <protocol type="pbcast.NAKACK"/>
  <protocol type="UNICAST2"/>
  <protocol type="pbcast.STABLE"/>
  <protocol type="pbcast.GMS"/>
  <protocol type="UFC"/>
  <protocol type="MFC"/>
  <protocol type="FRAG2"/>
  <protocol type="RSVP"/>
</stack>
```

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

[https://atl.kr/dokuwiki/doku.php/jboss\\_eap\\_6.x\\_tcp\\_clustering?rev=1508840074](https://atl.kr/dokuwiki/doku.php/jboss_eap_6.x_tcp_clustering?rev=1508840074)

Last update: **2017/10/24 10:14**

