

- JBoss EAP 7 Hot Deploy / Development mode** 3
- EAP 7.0.x*** 3
- EAP 7.1.x*** 3
- Development mode*** 3
- configuration** 4
- 5

JBoss EAP 7 Hot Deploy / Development mode

JSP	(Unmanaged)	. (WAR
가)		
Undertow	JSP	.

EAP 7.0.x

EAP 7.0.x	io.undertow.disable-file-system-watcher	true
-----------	---	------

```
JAVA_OPTS="$JAVA_OPTS -Dio.undertow.disable-file-system-watcher=true"
```

CLI

```
/system-property=io.undertow.disable-file-system-watcher:add(value=true)
```

EAP 7.1.x

EAP 7.1.0	undertow subsystem	disable-file-watch-service	true
-----------	--------------------	----------------------------	------

```
/subsystem=undertow/servlet-container=default:write-attribute(name=disable-file-watch-service,value=true)
```

Development mode

가	Undertow	.
---	----------	---

```
<subsystem xmlns="urn:jboss:domain:undertow:3.1">
  ...
  <servlet-container name="default">
    <jsp-config development="true"/>
    <websockets/>
  </servlet-container>
</subsystem>
```

CLI . check-interval modification-
test-interval 가

```
/subsystem=undertow/servlet-container=default/setting=jsp:write-attribute(name=development,value=true)
/subsystem=undertow/servlet-container=default/setting=jsp:write-attribute(name=recompile-on-fail,value=true)
/subsystem=undertow/servlet-container=default/setting=jsp:write-attribute(name=check-interval,value=60)
/subsystem=undertow/servlet-container=default/setting=jsp:write-attribute(name=modification-test-interval,value=60)
```

configuration

configuration xml
가

```
...
<subsystem xmlns="urn:jboss:domain:undertow:3.1">
  <buffer-cache name="default"/>
  <server name="default-server">
    <http-listener name="default" socket-binding="http"
redirect-socket="https"/>
    <host name="default-host" alias="localhost">
      <filter-ref name="server-header"/>
      <filter-ref name="x-powered-by-header"/>
    </host>
  </server>
  <servlet-container name="default">
    <!-- -->
    <jsp-config development="true" check-interval="1"
modification-test-interval="1" recompile-on-fail="true"/>
    <!-- -->
    <websockets/>
  </servlet-container>
  <handlers>
    <file name="welcome-content"
path="{jboss.home.dir}/welcome-content"/>
  </handlers>
  <filters>
    <response-header name="server-header" header-name="Server"
header-value="JBoss-EAP/7"/>
    <response-header name="x-powered-by-header" header-name="X-
Powered-By" header-value="Undertow/1"/>
  </filters>

```

```
</subsystem>
```

```
...
```

- CLI

```
/subsystem=undertow/servlet-container=default/setting=jsp:write-attribute(name=development,value=true)
/subsystem=undertow/servlet-container=default/setting=jsp:write-attribute(name=recompile-on-fail,value=true)
/subsystem=undertow/servlet-container=default/setting=jsp:write-attribute(name=check-interval,value=1)
/subsystem=undertow/servlet-container=default/setting=jsp:write-attribute(name=modification-test-interval,value=1)
```

- <https://access.redhat.com/solutions/3085681>
- <http://tyboss.tistory.com/entry/JBoss-%EB%B0%B0%ED%8F%AC%EB%90%9C-jboss-application-jsp-%EC%88%98%EC%A0%95-%EC%8B%9C-%EB%B0%94%EB%A1%9C-%EB%B0%98%EC%98%81>
- <http://stackoverflow.com/questions/31795274/how-do-i-enable-on-the-fly-compilation-of-jsps-in-wildfly-9>

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/jboss_eap_7_hot_deploy_development_mode_%EC%84%A4%EC%A0%95

Last update: **2020/02/19 02:07**

