


- JBoss EAP 7 Reverse Proxy** 3
 - 가 3
 - 4
 - 가 4
- default-server** 가 4
 - 4
 - 5

JBoss EAP 7 Reverse Proxy



가 WAS DB

가 WEB - / WAS DB

- JBoss EAP 7.x
- JBoss EAP 6.x
 - mod_jk
 - Apache httpd
 - mod_proxy, mod_cluster

가 Undertow 가

```
/subsystem=undertow/configuration=handler/reverse-proxy=LBProxy/:add(cached-connections-per-thread=5,connection-idle-timeout=60,connections-per-thread=10,max-request-time=-1,problem-server-retry=30,request-queue-size=10,session-cookie-names=JSESSIONID)
```

가 .

- : 10.10.10.10
- : 8109 (AJP)

```
/socket-binding-group=standard-sockets/remote-destination-outbound-socket-binding=backend-host1/:add(host=10.10.10.10,port=8109)
```

가

가 .

- : /TestApp
- ID : node1

```
/subsystem=undertow/configuration=handler/reverse-proxy=LBProxy/host=backend-host1/:add(instance-id=node1,outbound-socket-binding=backend-host1,path=/TestApp,scheme=ajp)
```

default-server

가

가 .

```
/subsystem=undertow/server=default-server/host=default-host/location=/TestApp/:add(handler=LBProxy)
```

XML .

- Undertow

```
<subsystem xmlns="urn:jboss:domain:undertow:3.1">
```

```
<buffer-cache name="default"/>
<server name="default-server">
  <http-listener name="default" socket-binding="http" redirect-
socket="https"/>
  <host name="default-host" alias="localhost">
    <location name="/" handler="welcome-content"/>
    <location name="/TestApp" handler="LBProxy"/>
    <filter-ref name="server-header"/>
    <filter-ref name="x-powered-by-header"/>
  </host>
</server>
<servlet-container name="default">
  <jsp-config/>
  <websockets/>
</servlet-container>
<handlers>
  <file name="welcome-content" path="{jboss.home.dir}/welcome-
content"/>
  <reverse-proxy name="LBProxy" connection-idle-timeout="60">
    <host name="backend-host1" outbound-socket-binding="backend-
host1" scheme="ajp" path="/TestApp" instance-id="node1"/>
  </reverse-proxy>
</handlers>
<filters>
  <response-header name="server-header" header-name="Server" header-
value="JBoss-EAP/7"/>
  <response-header name="x-powered-by-header" header-name="X-Powered-
By" header-value="Undertow/1"/>
</filters>
</subsystem>
```

-

```
<outbound-socket-binding name="backend-host1">
  <remote-destination host="1.1.1.1" port="8109"/>
</outbound-socket-binding>
```

가 <http://localhost:8080/TestApp> 가

- <https://access.redhat.com/solutions/2463121>

Last update: jboss_eap_7_reverse_proxy - https://atl.kr/dokuwiki/doku.php/jboss_eap_7_reverse_proxy_%EA%B5%AC%EC%84%B1?rev=1584412634
2020/03/17 02:37

From:
<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:
https://atl.kr/dokuwiki/doku.php/jboss_eap_7_reverse_proxy_%EA%B5%AC%EC%84%B1?rev=1584412634

Last update: **2020/03/17 02:37**

