


- JBoss EAP 7 Reverse Proxy** ..... 3
- 가 ..... 4
- ..... 4
- 가 ..... 4
- default-server** 가 ..... 4
- ..... 5
- ..... 6



# JBoss EAP 7 Reverse Proxy

— 2026/04/13 05:35



가  
 WAS DB  
 WEB - / WAS  
 DB

- JBoss EAP 7.x
- JBoss EAP 6.x  
mod\_jk

Apache httpd

. mod\_proxy, mod\_cluster

Warning icon: 10.10.10.10 WAS WAS

## 가

Undertow

가

```
/subsystem=undertow/configuration=handler/reverse-proxy=LBProxy/:add(cached-connections-per-thread=5,connection-idle-timeout=60,connections-per-thread=10,max-request-time=-1,problem-server-retry=30,request-queue-size=10,session-cookie-names=JSESSIONID)
```

가

- : 10.10.10.10
- : 8109 (AJP)

```
/socket-binding-group=standard-sockets/remote-destination-outbound-socket-binding=backend-host1/:add(host=10.10.10.10,port=8109)
```

## 가

가

- : /TestApp
- ID : node1

```
/subsystem=undertow/configuration=handler/reverse-proxy=LBProxy/host=backend-host1/:add(instance-id=node1,outbound-socket-binding=backend-host1,path=/TestApp,scheme=ajp)
```

## default-server

가

가

```
/subsystem=undertow/server=default-server/host=default-host/location=\/TestApp/:add(handler=LBProxy)
```

## XML

- Undertow

```
<subsystem xmlns="urn:jboss:domain:undertow:3.1">
  <buffer-cache name="default"/>
  <server name="default-server">
    <http-listener name="default" socket-binding="http" redirect-socket="https"/>
    <host name="default-host" alias="localhost">
      <location name="/" handler="welcome-content"/>
      <location name="/TestApp" handler="LBProxy"/>
      <filter-ref name="server-header"/>
      <filter-ref name="x-powered-by-header"/>
    </host>
  </server>
  <servlet-container name="default">
    <jsp-config/>
    <websockets/>
  </servlet-container>
  <handlers>
    <file name="welcome-content" path="${jboss.home.dir}/welcome-content"/>
    <reverse-proxy name="LBProxy" connection-idle-timeout="60">
      <host name="backend-host1" outbound-socket-binding="backend-host1" scheme="ajp" path="/TestApp" instance-id="node1"/>
    </reverse-proxy>
  </handlers>
  <filters>
    <response-header name="server-header" header-name="Server" header-value="JBoss-EAP/7"/>
    <response-header name="x-powered-by-header" header-name="X-Powered-By" header-value="Undertow/1"/>
  </filters>
</subsystem>
```

- 

```
<outbound-socket-binding name="backend-host1">
  <remote-destination host="10.10.10.10" port="8109"/>
</outbound-socket-binding>
```

가 <http://localhost:8080/TestApp> 가

Last update: jboss\_eap\_7\_reverse\_proxy - [https://atl.kr/dokuwiki/doku.php/jboss\\_eap\\_7\\_reverse\\_proxy\\_%EA%B5%AC%EC%84%B1?rev=1776061645](https://atl.kr/dokuwiki/doku.php/jboss_eap_7_reverse_proxy_%EA%B5%AC%EC%84%B1?rev=1776061645)  
2026/04/13 06:27

---

- <https://access.redhat.com/solutions/2463121>

From:  
<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:  
[https://atl.kr/dokuwiki/doku.php/jboss\\_eap\\_7\\_reverse\\_proxy\\_%EA%B5%AC%EC%84%B1?rev=1776061645](https://atl.kr/dokuwiki/doku.php/jboss_eap_7_reverse_proxy_%EA%B5%AC%EC%84%B1?rev=1776061645)

Last update: **2026/04/13 06:27**

