

- JBoss EAP General configuration script** 3
- add-user.sh*** 3
- jboss.env*** 3
- jboss.properties*** 7
- jboss-cli.sh*** 7
- kill.sh*** 8
- shutdown.sh*** 9
- start.sh*** 10
- sysctl.conf*** 11

JBoss EAP General configuration script

add-user.sh

```
#!/bin/sh
ABSOLUTE_PATH="$(cd $(dirname "$0") && pwd -P)"
PROFILE_PATH="${ABSOLUTE_PATH%/*}"
DIR_NAME="${PROFILE_PATH##*/}" # bin dir
#DIR_NAME="${ABSOLUTE_PATH##*/}" # root dir

. $ABSOLUTE_PATH/jboss.env

JAVA_OPTS="$JAVA_OPTS -
Djboss.server.config.user.dir=$SERVER_BASE_DIR/configuration "

#$JBOSS_HOME/bin/add-user.sh @$@
$JBOSS_HOME/bin/add-user.sh
```

jboss.env

```
#####
# description : JBoss EAP 7.x Standalone
# date       : 2017-05-11
# author     : kwlee2@linuxdata.co.kr
#####
DATE=`date "+%Y%m%d_%H%M%S"`
UNAME=`id -u -n`

JBOSS_USER="root"
NODE_NAME="node11"

#####
# JBOSS Common Setup
#####
JBOSS_HOME="/software/jboss7"

SERVER_HOME="$JBOSS_HOME/SERVERS"
SERVER_BASE_DIR="$SERVER_HOME/$NODE_NAME"

LOG_HOME="$SERVER_BASE_DIR/logs"

BIND_ADDR="192.168.0.73"
MGNT_ADDR="192.168.0.73"
PRIVATE_ADDR="192.168.0.73"
UNSECURE_ADDR="127.0.0.1"
```

```
MULTICAST_ADDR="230.0.0.3"
CLUSTER_PASSWD="CHANGEME!!"
MESSAGE_ADDR="231.7.10.1"
MESSAGE_PORT="9876"

MGNT_HTTP_PORT="9990"
MGNT_HTTPS_PORT="9993"

PORT_OFFSET="0"
PORT_AJP="8009"
PORT_HTTP="8080"
PORT_HTTPS="8443"

#####
# Current Host Setup
#####
GC_TYPE="g1"      # "cms", "parallel", "g1"(only jdk 7u4 or greater)
USE_LARGE_PAGE="false" # "true", "false"

#####
# Configuration File
#####
SERVER_CONFIG_FILE="standalone-full-ha.xml"

#####
# Java Version Check
JAVA_VER=$(java -version 2>&1 | grep -i version | sed 's/.*version
.*\.\(.*\)\\.*/\1/; lq')
if [ -z "$JAVA_VER" ]
then
    echo "Java is not installed"
    exit 1
fi

#####
# JVM Options
#####
JAVA_OPTS="-DNODE_NAME=$NODE_NAME"
JAVA_OPTS="$JAVA_OPTS -server"
JAVA_OPTS="$JAVA_OPTS -XX:+DoEscapeAnalysis"
JAVA_OPTS="$JAVA_OPTS -Xms2048m"
JAVA_OPTS="$JAVA_OPTS -Xmx4096m"

### Garbage Collection Options
JAVA_OPTS="$JAVA_OPTS -verbose:gc"
JAVA_OPTS="$JAVA_OPTS -Xloggc:$LOG_HOME/gc_$DATE.log"
JAVA_OPTS="$JAVA_OPTS -XX:+PrintGCDetails"
JAVA_OPTS="$JAVA_OPTS -XX:+PrintGCTimeStamps"
JAVA_OPTS="$JAVA_OPTS -XX:+PrintGCApplicationStoppedTime"
```

```
JAVA_OPTS="$JAVA_OPTS -XX:+HeapDumpOnOutOfMemoryError"
JAVA_OPTS="$JAVA_OPTS -XX:HeapDumpPath=$LOG_HOME/"

# Use on x86_64
JAVA_OPTS="$JAVA_OPTS -XX:+UseCompressedOops"

### Collector type : CMS(low pause)
if [ $GC_TYPE == "cms" ]; then
    JAVA_OPTS="$JAVA_OPTS -XX:+UseConcMarkSweepGC"
    JAVA_OPTS="$JAVA_OPTS -XX:+CMSClassUnloadingEnabled"
    JAVA_OPTS="$JAVA_OPTS -XX:+UseParNewGC"
    JAVA_OPTS="$JAVA_OPTS -XX:+ExplicitGCInvokesConcurrent"
    JAVA_OPTS="$JAVA_OPTS -XX:CMSInitiatingOccupancyFraction=80"
    JAVA_OPTS="$JAVA_OPTS -XX:CMSIncrementalSafetyFactor=20"
    JAVA_OPTS="$JAVA_OPTS -XX:+UseCMSInitiatingOccupancyOnly"

### Collector type : Parallel (throughput)
elif [ $GC_TYPE == "parallel" ]; then
    JAVA_OPTS="$JAVA_OPTS -XX:+UseParallelGC"
    JAVA_OPTS="$JAVA_OPTS -XX:+UseParallelOldGC"

### Collector type : G1 (low pause) ONLY USE for JDK 7u4 or greater
elif [ $GC_TYPE == "g1" ]; then
    JAVA_OPTS="$JAVA_OPTS -XX:+UseG1GC"
    JAVA_OPTS="$JAVA_OPTS -XX:+ExplicitGCInvokesConcurrent"
    JAVA_OPTS="$JAVA_OPTS -XX:MaxGCPauseMillis=500"

else
    echo "ERROR: GC_TYPE is NOT SET!!!";
    exit 0;
fi

#####
# Java Version setting
if [ $JAVA_VER -ge 8 ]; then
    JAVA_OPTS="$JAVA_OPTS -XX:+UseCompressedClassPointers"
    JAVA_OPTS="$JAVA_OPTS -XX:CompressedClassSpaceSize=1024M"
    JAVA_OPTS="$JAVA_OPTS -XX:MetaspaceSize=512M"
    JAVA_OPTS="$JAVA_OPTS -XX:MaxMetaspaceSize=512M"
elif [ $JAVA_VER -le 7 ]; then
    JAVA_OPTS="$JAVA_OPTS -XX:PermSize=256M"
    JAVA_OPTS="$JAVA_OPTS -XX:MaxPermSize=256M"
fi

### Linux Large Page Setting
if [ $USE_LARGEPAGE == "true" ]; then
    JAVA_OPTS="$JAVA_OPTS -XX:+UseLargePages";
fi

JAVA_OPTS="$JAVA_OPTS -Djava.awt.headless=true"
JAVA_OPTS="$JAVA_OPTS -Djava.net.preferIPv4Stack=true"
```

```
JAVA_OPTS="$JAVA_OPTS -Dorg.jboss.resolver.warning=true"

### byteman
JAVA_OPTS="$JAVA_OPTS -Djboss.modules.system.pkgs=org.jboss.byteman"

#####
# Bind Address
#####
JAVA_OPTS="$JAVA_OPTS -Djboss.bind.address=$BIND_ADDR"
JAVA_OPTS="$JAVA_OPTS -Djboss.bind.address.management=$MGNT_ADDR"
JAVA_OPTS="$JAVA_OPTS -Djboss.bind.address.private=$PRIVATE_ADDR"
JAVA_OPTS="$JAVA_OPTS -Djboss.bind.address.unsecure=$UNSECURE_ADDR"

JAVA_OPTS="$JAVA_OPTS -Djboss.default.multicast.address=$MULTICAST_ADDR"
JAVA_OPTS="$JAVA_OPTS -Djboss.messaging.cluster.password=$CLUSTER_PASSWD"
JAVA_OPTS="$JAVA_OPTS -Djboss.messaging.group.address=$MESSAGE_ADDR"
JAVA_OPTS="$JAVA_OPTS -Djboss.messaging.group.port=$MESSAGE_PORT"

# Management
JAVA_OPTS="$JAVA_OPTS -Djboss.management.http.port=$MGNT_HTTP_PORT"
JAVA_OPTS="$JAVA_OPTS -Djboss.management.https.port=$MGNT_HTTPS_PORT"

# Port Offset
JAVA_OPTS="$JAVA_OPTS -Djboss.socket.binding.port-offset=$PORT_OFFSET"

# Ports
JAVA_OPTS="$JAVA_OPTS -Djboss.ajp.port=$PORT_AJP"
JAVA_OPTS="$JAVA_OPTS -Djboss.http.port=$PORT_HTTP"
JAVA_OPTS="$JAVA_OPTS -Djboss.https.port=$PORT_HTTPS"

# modcluster proxy list
#JAVA_OPTS="$JAVA_OPTS -
Djboss.mod_cluster.proxyList=address1:port1,address2:port2"
#JAVA_OPTS="$JAVA_OPTS -
Djboss.mod_cluster.excludedContexts=host1:context1,host2:context2,host3:cont
ext3"
#JAVA_OPTS="$JAVA_OPTS -Djboss.mod_cluster.jvmRoute="

### JBoss Env Setting - Global
#JAVA_OPTS="$JAVA_OPTS -Djboss.qualified.host.name=$NODE_NAME"
JAVA_OPTS="$JAVA_OPTS -Djboss.home.dir=$JBOSS_HOME"
JAVA_OPTS="$JAVA_OPTS -Djboss.host.name=$NODE_NAME"
JAVA_OPTS="$JAVA_OPTS -Djboss.host.default.config=$HOST_CONFIG_FILE"
JAVA_OPTS="$JAVA_OPTS -Djboss.node.name=$NODE_NAME"
JAVA_OPTS="$JAVA_OPTS -DjvmRoute=$NODE_NAME"
JAVA_OPTS="$JAVA_OPTS -Djboss.tx.node.id=$NODE_NAME"
JAVA_OPTS="$JAVA_OPTS -Dorg.jboss.boot.log.file=$LOG_HOME/boot.log"

### JBoss Env Setting - Standalone mode
```

```

JAVA_OPTS="$JAVA_OPTS -Djboss.server.base.dir=$SERVER_BASE_DIR"
JAVA_OPTS="$JAVA_OPTS -Djboss.server.default.config=$SERVER_CONFIG_FILE"
JAVA_OPTS="$JAVA_OPTS -Djboss.server.log.dir=$LOG_HOME"

JAVA_OPTS="$JAVA_OPTS -Djava.library.path=$LD_LIBRARY_PATH"

### Custom Settings
#JAVA_OPTS="$JAVA_OPTS -
Dlogging.configuration=file:CONF_DIR/logging.properties"

export JAVA_OPTS

echo "=====
echo "JBOSS_HOME=$JBOSS_HOME"
echo "SERVER_HOME=$SERVER_HOME"
echo "NODE_NAME=$NODE_NAME"
echo "HOST_ADDR=$HOST_ADDR"
echo "SERVER_CONFIG_FILE=$SERVER_CONFIG_FILE"
echo "JAVA_OPTS=$JAVA_OPTS"
echo "LD_LIBRARY_PATH=$LD_LIBRARY_PATH"
echo "=====

# EOF

```

jboss.properties

```

JBoss EAP 7          org.apache.catalina.connector.URI_ENCODING=UTF-8
org.apache.catalina.connector.USE_BODY_ENCODING_FOR_QUERY_STRING=true   가
가
.

```

```

org.apache.catalina.connector.URI_ENCODING=UTF-8
org.apache.catalina.connector.USE_BODY_ENCODING_FOR_QUERY_STRING=true
org.hornetq.core.message.impl.HDR_DUPLICATE_DETECTION_ID=$NODE_NAME

```

jboss-cli.sh

```

#!/bin/sh
#####
# instance      : template
# description   : instance start script
# date         : 2014-10-07
# author       : kwlee2@linuxdata.co.kr
#####
ABSOLUTE_PATH="$(cd $(dirname "$0") && pwd -P)"
DIR_NAME="${ABSOLUTE_PATH##*/}"

```

```
. $ABSOLUTE_PATH/jboss.env

#export JAVA_OPTS="$JAVA_OPTS -Djava.awt.headless=false "

if [ "$MGNT_ADDR" == "0.0.0.0" ]
then
    MGNT_ADDR=127.0.0.1
fi

echo "$JBASS_HOME/bin/jboss-cli.sh --
controller=$MGNT_ADDR:$((MGNT_HTTP_PORT + PORT_OFFSET)) --connect @$@"
$JBASS_HOME/bin/jboss-cli.sh --controller=$MGNT_ADDR:$((MGNT_HTTP_PORT +
PORT_OFFSET)) --connect @$@"
```

kill.sh

```
#!/bin/sh
#####
# instance      : template
# description   : instance start script
# date         : 2014-10-07
# author       : kwlee2@linuxdata.co.kr
#####
ABSOLUTE_PATH="$(cd $(dirname "$0") && pwd -P)"
DIR_NAME="${ABSOLUTE_PATH##*/}"

. $ABSOLUTE_PATH/jboss.env

PID=`ps -ef | grep java | grep "NODE_NAME=$NODE_NAME" | grep
"jboss.server.base.dir=$SERVER_BASE_DIR" | awk '{print $2}'`
echo $PID

if [ "$PID" == "" ]
then
    echo "JBoss SERVER - [$NODE_NAME] is NOT RUNNING..."
    exit 1;
fi

#ps -ef | grep java | grep "NODE_NAME=$NODE_NAME" | grep
"jboss.server.base.dir=$SERVER_BASE_DIR" | awk '{print "kill -9 " $2}' | sh
-x
kill -9 $PID

echo "Killing down SERVER $NODE_NAME..."
sleep 10
```


shutdown.sh

```
#!/bin/sh
#####
# instance      : template
# description   : instance start script
# date          : 2014-10-07
# author        : kwlee2@linuxdata.co.kr
#####
ABSOLUTE_PATH="$(cd $(dirname "$0") && pwd -P)"
DIR_NAME="${ABSOLUTE_PATH##*/}"

. $ABSOLUTE_PATH/jboss.env

PID=`ps -ef | grep java | grep "NODE_NAME=$NODE_NAME " | awk '{print $2}'`
echo $PID

if [ "$PID" == "" ]
then
    echo "JBoss SERVER - [$NODE_NAME] is NOT RUNNING..."
    exit 1;
fi

echo -n "Account:"
read USERNAME
echo -n "Password:"
read -s PASSWORD
echo ""

if [ "$PORT_OFFSET" != "" ]
then
    MGNT_HTTP_PORT=$(( $MGNT_HTTP_PORT + $PORT_OFFSET ))
fi

if [ "$MGNT_ADDR" == "0.0.0.0" ]
then
    MGNT_ADDR="127.0.0.1"
fi

echo "$JBASS_HOME/bin/jboss-cli.sh --connect --
controller=$MGNT_ADDR:$MGNT_HTTP_PORT --user=$USERNAME --password=$PASSWORD
--command=shutdown"
$JBASS_HOME/bin/jboss-cli.sh --connect --
controller=$MGNT_ADDR:$MGNT_HTTP_PORT --user=$USERNAME --password=$PASSWORD
--command=shutdown

if [ $? != 0 ]
then
    exit 1
fi
```

```
echo "Server $NODE_NAME Shutting Down..."
while true
do
PID=`ps -ef | grep java | grep "NODE_NAME=$NODE_NAME " | awk '{print $2}'`
echo "PID:$PID"

    if [ "$PID" == "" ]
    then
        break
    fi
    sleep 2
done
echo "Done."
```

start.sh

```
#!/bin/sh
#####
# instance      : template
# description   : instance start script
# date         : 2014-10-07
# author       : kwlee2@linuxdata.co.kr
#####
ABSOLUTE_PATH="$(cd $(dirname "$0") && pwd -P)"
DIR_NAME="${ABSOLUTE_PATH##*/}"

. $ABSOLUTE_PATH/jboss.env

PID=`ps -ef | grep java | grep "NODE_NAME=$NODE_NAME " | awk '{print $2}'`
echo $PID

if [ "$PID" != "" ]
then
    echo "JBoss SERVER - [$NODE_NAME] is already RUNNING..."
    exit 1;
fi

if [ -z "$NODE_NAME" ]
then
    echo -e "\e[33mWARNING\e[0m : \e[32mjboss.env is not configured.\e[0m"
    echo -e "\e[33mWARNING\e[0m : Program Exit."
    exit 1
fi

if [ "$DIR_NAME" != "$NODE_NAME" ]
then
    echo -e "\e[33mWARNING\e[0m : \e[32mDIRECTORY and NODE_NAME are not
```

```
same\e[0m"
    echo -e "\e[33mWARNING\e[0m : Program Exit."
    exit 2
fi

if [ "$JBOSS_USER" != "$UNAME" ]
then
    echo -e "\e[33mWARNING\e[0m : Current User is [\e[31m$UNAME\e[0m]. MUST
run to [\e[32m$JBOSS_USER\e[0m]."
    echo -e "\e[33mWARNING\e[0m : Program Exit."
    exit 3
fi

if [ ! -e "$JBOSS_HOME" -o ! -e "$SERVER_HOME" ]; then
    echo "JBOSS_HOME or SERVER_HOME is not Exists";
    exit 4
fi

if [ ! -d "$LOG_HOME" ]; then
    mkdir -p $LOG_HOME
fi

nohup $JBOSS_HOME/bin/standalone.sh -P=$SERVER_BASE_DIR/jboss.properties >>
$LOG_HOME/jboss_console.log 2>&1 &

exit 0
# EOF
```

sysctl.conf

```
# Allow a 25MB UDP receive buffer for JGroups
net.core.rmem_max = 26214400
# Allow a 1MB UDP send buffer for JGroups
net.core.wmem_max = 1048576

#
net.core.rmem_default = 26214400
net.core.wmem_default = 1048576
```

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/jboss_eap_general_configuration_script?rev=1582779546

Last update: **2020/02/27 04:59**

