

JBoss Systemd 3

JBoss Systemd

```
/etc/systemd/system          jboss@.service
```

- `systemctl start jboss@instance.service`
- `instance`

```
[Unit]
Description=JBoss EAP 7.4 - instance %i
After=syslog.target network.target

[Service]
Type=forking

WorkingDirectory=/data/jboss/SERVERS/%i
#Environment="JAVA_HOME=/usr/lib/jvm/java-1.8.0-
openjdk-1.8.0.262.b10-0.el7_8.x86_64/"
#Environment="JBOSS_HOME=/usr/local/server/jboss"
#Environment="JBOSS_BASE=/usr/local/server/jboss"
#Environment="JABA_OPTS=-Xms512M -Xmx1024M -server -XX:+UseParallelGC -
Djava.security.egd=file:///dev/urandom"

ExecStart=/bin/sh /data/jboss/SERVERS/%i/bin/start.sh
ExecStop=/bin/sh /data/jboss/SERVERS/%i/bin/shutdown.sh

User=root
Group=root
UMask=0022
RestartSec=10
TimeoutStopSec=10

#Restart=always

[Install]
WantedBy=multi-user.target
```

```
systemd
```

```
[root@host ~]# systemctl daemon-reload
[root@host ~]# systemctl enable jboss@node11.service
```

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/jboss_systemd_%EB%93%B1%EB%A1%9D

Last update: **2023/01/09 11:25**

