

**JBoss / Wildfly mod\_cluster** ..... 3



# JBoss / Wildfly mod\_cluster

- [https://docs.wildfly.org/26.1/High\\_Availability\\_Guide.html](https://docs.wildfly.org/26.1/High_Availability_Guide.html)

```
jvmRoute(instance-id)
```

```
[standalone@localhost:9990 /] /subsystem=undertow:write-attribute(name=instance-id,value=myroute)
{
  "outcome" => "success",
  "response-headers" => {
    "operation-requires-reload" => true,
    "process-state" => "reload-required"
  }
}
```

```
/subsystem=modcluster/proxy=default:write-attribute(name=proxy-list,
value="192.168.0.141:6666,192.168.0.142:6666")
/subsystem=modcluster/proxy=default/load-provider=dynamic/load-
metric=cpu:write-attribute(name=type,value=busyness)

# balancer name
/subsystem=modcluster/proxy=default:write-attribute(name=balancer,
value=mycluster)
```

From:  
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:  
[https://atl.kr/dokuwiki/doku.php/jboss\\_wildfly\\_mod\\_cluster\\_%EC%84%A4%EC%A0%95?rev=1706837637](https://atl.kr/dokuwiki/doku.php/jboss_wildfly_mod_cluster_%EC%84%A4%EC%A0%95?rev=1706837637)

Last update: 2024/02/02 01:33

