

Jitsi meet	3
	3
Prosody	3
Jitsi	3
()	3
Jitsi Meet	3
	4
	4
Prosody	4
Jitsi Meet	4
Jicofo	5
Prosody User	5
Branding	5
	6

Jitsi meet



(2022-06-16) jitsi Debian/Ubuntu
가 . RHEL/CentOS 가 가 .
(container 가)

```
apt install gnupg2 nginx-full sudo curl wget openjdk-11-jdk openjdk-17-jdk
update-alternatives --config java
```

Prosody

```
echo deb http://packages.prosody.im/debian $(lsb_release -sc) main | tee -a
/etc/apt/sources.list
wget https://prosody.im/files/prosody-debian-packages.key -O- | apt-key add
-
```

Jitsi

```
curl https://download.jitsi.org/jitsi-key.gpg.key | sh -c 'gpg --dearmor >
/usr/share/keyrings/jitsi-keyring.gpg'
echo 'deb [signed-by=/usr/share/keyrings/jitsi-keyring.gpg]
https://download.jitsi.org/stable/' | tee /etc/apt/sources.list.d/jitsi-
stable.list > /dev/null

# update all package sources
apt update
```

()

```
firewall-cmd --permanent --add-service=http --add-service=https
firewall-cmd --permanent --add-port=10000/udp --add-port=3478/udp --add-
port=5349/tcp
firewall-cmd --reload
```

Jitsi Meet

```
# jitsi-meet installation
apt install jitsi-meet
```

```
systemctl restart prosody
systemctl restart jicofo
systemctl restart jitsi-videobridge2

#
systemctl restart nginx
```

jitsi

Prosody

/etc/prosody/conf.avail/[your-hostname].cfg.lua

```
VirtualHost "jitsi-meet.example.com"
  -- enabled = false -- Remove this line to enable this host
  --authentication = "anonymous"
  authentication = "internal_hashed"
```

- 가 가

```
VirtualHost "guest.jitsi-meet.example.com"
  authentication = "anonymous"
  c2s_require_encryption = false
```

Jitsi Meet

/etc/jitsi/meet/[your-hostname]-config.js

```
var config = {
  hosts: {
    domain: 'jitsi-meet.example.com',
    anonymousdomain: 'guest.jitsi-meet.example.com',
    ...
  },
  ...
}
```

```
}
```

Jicofo

/etc/jitsi/jicofo/jicofo.conf

```
jicofo {
  authentication: {
    enabled: true
    type: XMPP
    login-url: jitsi-meet.example.com
  }
  ...
}
```

Prosody User

```
sudo prosodyctl register <username> jitsi-meet.example.com <password>

systemctl restart prosody
systemctl restart jicofo
systemctl restart jitsi-videobridge2
```

Branding

```
/etc/jitsi/meet/[your-hostname]-config.js      dynamicBrandingUrl:
'/static/brand/branding.json',                  가      .
```

```
nginx      URL/static/
```

```
/usr/share/jitsi-meet/static/      branding
```

```
/usr/share/jitsi-meet/static/brand/branding.json
```

```
{
  "backgroundColor": "#FFF",
  "backgroundImageUrl": "https://mycompany.com/images/background.png",
  "didPageUrl": "https://mycompany.com/dids",
  "inviteDomain": "https://mycompany.com/invite",
  "logoClickUrl": "https://mycompany.com",
  "logoImageUrl": "https://mycompany.com/images/logo.png",
  "avatarBackgrounds": ["#12A378", "linear-gradient(125.83deg, #000 0%, #FFF 99.09%)"],
}
```

```
"premeetingBackground":
"url(https://mycompany.com/images/premeetingBackground.png)",
"virtualBackgrounds": ["https://my.img01.jpg", "https://my.img02.jpg"],
"labels": {
  "en": "https://myenglishlabels.json",
  "fr": "https://myfrenchlabels.json",
  "ptBR": "https://mybrazilianlabels.json"
},
"customTheme": {
  "palette": {
    "ui01": "orange !important",
    "ui02": "maroon",
    "surface02": "darkgreen",
    "ui03": "violet",
    "ui04": "magenta",
    "ui05": "blueviolet",
    "field02Hover": "red",
    "action01": "green",
    "action01Hover": "lightgreen",
    "action02Disabled": "beige",
    "success02": "cadetblue",
    "action02Hover": "liceblue"
  },
  "typography": {
    "labelRegular": {
      "fontSize": 25,
      "lineHeight": 30,
      "fontWeight": 500
    }
  }
}
```

- <https://jitsi.github.io/handbook/docs/devops-guide/devops-guide-quickstart>
- <https://jitsi.github.io/handbook/docs/devops-guide/secure-domain>
- <https://developer.8x8.com/jaas/docs/jaas-prefs-advanced-branding>

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/jitsi_meet_%EC%84%A4%EC%B9%98_%EB%A7%A4%EB%89%B4%EC%96%BC?rev=1655799429

Last update: 2022/06/21 08:17

