

- Jitsi meet** 3
- 3
- Prosody 3
- Jitsi 3
- () 3
- Jitsi Meet 3
- 4
- 4
- Prosody 4
- Jitsi Meet 4
- Jicofo 5
- Prosody User 5
- Branding** 5
- 6
- 7

Jitsi meet



(2022-06-16) jitsi Debian/Ubuntu
 가 . RHEL/CentOS 가 가 .
 (container 가)

```
apt install gnupg2 nginx-full sudo curl wget openjdk-11-jdk openjdk-17-jdk
update-alternatives --config java
```

Prosody

```
echo deb http://packages.prosody.im/debian $(lsb_release -sc) main | tee -a
/etc/apt/sources.list
wget https://prosody.im/files/prosody-debian-packages.key -O- | apt-key add
-
```

Jitsi

```
curl https://download.jitsi.org/jitsi-key.gpg.key | sh -c 'gpg --dearmor >
/usr/share/keyrings/jitsi-keyring.gpg'
echo 'deb [signed-by=/usr/share/keyrings/jitsi-keyring.gpg]
https://download.jitsi.org/stable/' | tee /etc/apt/sources.list.d/jitsi-
stable.list > /dev/null

# update all package sources
apt update
```

()

```
firewall-cmd --permanent --add-service=http --add-service=https
firewall-cmd --permanent --add-port=10000/udp --add-port=3478/udp --add-
port=5349/tcp
firewall-cmd --reload
```

Jitsi Meet

```
# jitsi-meet installation
apt install jitsi-meet
```

```
systemctl restart prosody
systemctl restart jicofo
systemctl restart jitsi-videobridge2

#
systemctl restart nginx
```

jitsi

Prosody

/etc/prosody/conf.avail/[your-hostname].cfg.lua

```
VirtualHost "jitsi-meet.example.com"
  -- enabled = false -- Remove this line to enable this host
  --authentication = "anonymous"
  authentication = "internal_hashed"
```

- 가 가

```
VirtualHost "guest.jitsi-meet.example.com"
  authentication = "anonymous"
  c2s_require_encryption = false
```

Jitsi Meet

/etc/jitsi/meet/[your-hostname]-config.js

```
var config = {
  hosts: {
    domain: 'jitsi-meet.example.com',
    anonymousdomain: 'guest.jitsi-meet.example.com',
    ...
  },
  ...
}
```

```
}
```

Jicofo

/etc/jitsi/jicofo/jicofo.conf

```
jicofo {
  authentication: {
    enabled: true
    type: XMPP
    login-url: jitsi-meet.example.com
  }
  ...
}
```

Prosody User

```
sudo prosodyctl register <username> jitsi-meet.example.com <password>

systemctl restart prosody
systemctl restart jicofo
systemctl restart jitsi-videobridge2
```

Branding

```
/etc/jitsi/meet/[your-hostname]-config.js      dynamicBrandingUrl:
'/static/brand/branding.json',                가 .
```

```
nginx                                          URL/static/
```

```
/usr/share/jitsi-meet/static/                branding
```

```
/usr/share/jitsi-meet/static/brand/branding.json
```

```
{
  "backgroundColor": "#FFF",
  "backgroundImageUrl": "https://mycompany.com/images/background.png",
  "didPageUrl": "https://mycompany.com/dids",
  "inviteDomain": "https://mycompany.com/invite",
  "logoClickUrl": "https://mycompany.com",
  "logoImageUrl": "https://mycompany.com/images/logo.png",
  "avatarBackgrounds": ["#12A378", "linear-gradient(125.83deg, #000 0%, #FFF 99.09%)"],
}
```

```
"premeetingBackground":  
"url(https://mycompany.com/images/premeetingBackground.png)",  
"virtualBackgrounds": ["https://my.img01.jpg", "https://my.img02.jpg"],  
"labels": {  
  "en": "https://myenglishlabels.json",  
  "fr": "https://myfrenchlabels.json",  
  "ptBR": "https://mybrazilianlabels.json"  
},  
"customTheme": {  
  "palette": {  
    "ui01": "orange !important",  
    "ui02": "maroon",  
    "surface02": "darkgreen",  
    "ui03": "violet",  
    "ui04": "magenta",  
    "ui05": "blueviolet",  
    "field02Hover": "red",  
    "action01": "green",  
    "action01Hover": "lightgreen",  
    "action02Disabled": "beige",  
    "success02": "cadetblue",  
    "action02Hover": "liceblue"  
  },  
  "typography": {  
    "labelRegular": {  
      "fontSize": 25,  
      "lineHeight": 30,  
      "fontWeight": 500  
    }  
  }  
}  
}
```

```
prosodyctl /  
          /var/lib/prosody/*/accounts  
가 .
```

```
ls /var/lib/prosody/*/accounts|grep .dat|sed s/'.dat'//g
```

```
가 가 .
```

```
curl -OJL http://prosody.im/files/mod_listusers.lua  
chmod 755 mod_listusers.lua  
mv mod_listusers.lua /usr/lib/prosody/modules/
```

- <https://partage.les-miquelots.net/engver/blog/list-accounts-created-with-prosodyctl.html>

- <https://jitsi.github.io/handbook/docs/devops-guide/devops-guide-quickstart>
- <https://jitsi.github.io/handbook/docs/devops-guide/secure-domain>
- <https://developer.8x8.com/jaas/docs/jaas-prefs-advanced-branding>

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/jitsi_meet_%EC%84%A4%EC%B9%98_%EB%A7%A4%EB%89%B4%EC%96%BC?rev=1663294611

Last update: **2022/09/16 02:16**

