

Jitsi meet

.....

3

.....

3

Prosody

.....

3

Jitsi

.....

3

()

.....

3

Jitsi Meet

.....

3

.....

4

.....

4

Prosody

.....

4

Jitsi Meet

.....

4

Jicofo

.....

5

Prosody User

.....

5

Branding

.....

5

.....

6

.....

7

Jitsi meet



(2022-06-16) jitsi Debian/Ubuntu
가 . RHEL/CentOS 가 가 .
(container 가)

```
apt install gnupg2 nginx-full sudo curl wget openjdk-11-jdk openjdk-17-jdk
update-alternatives --config java
```

Prosody

```
echo deb http://packages.prosody.im/debian $(lsb_release -sc) main | sudo
tee -a /etc/apt/sources.list
wget https://prosody.im/files/prosody-debian-packages.key -O- | sudo apt-key
add -
apt install lua5.2
```

Jitsi

```
curl https://download.jitsi.org/jitsi-key.gpg.key | sudo sh -c 'gpg --
dearmor > /usr/share/keyrings/jitsi-keyring.gpg'
echo 'deb [signed-by=/usr/share/keyrings/jitsi-keyring.gpg]
https://download.jitsi.org stable/' | sudo tee
/etc/apt/sources.list.d/jitsi-stable.list > /dev/null

# update all package sources
apt update
```

()

```
firewall-cmd --permanent --add-service=http --add-service=https
firewall-cmd --permanent --add-port=10000/udp --add-port=3478/udp --add-
port=5349/tcp
firewall-cmd --reload
```

Jitsi Meet

```
# jitsi-meet installation
apt install jitsi-meet
```

```
systemctl restart prosody
systemctl restart jicofo
systemctl restart jitsi-videobridge2

#
systemctl restart nginx
```

jitsi

Prosody

/etc/prosody/conf.avail/[your-hostname].cfg.lua

```
VirtualHost "jitsi-meet.example.com"
  -- enabled = false -- Remove this line to enable this host
  --authentication = "anonymous"
  authentication = "internal_hashed"
```

- 가 가

```
VirtualHost "guest.jitsi-meet.example.com"
  authentication = "anonymous"
  c2s_require_encryption = false
```

Jitsi Meet

/etc/jitsi/meet/[your-hostname]-config.js

```
var config = {
  hosts: {
    domain: 'jitsi-meet.example.com',
    anonymousdomain: 'guest.jitsi-meet.example.com',
    ...
  }
}
```

```

    },
    ...
}

```

Jicofo

/etc/jitsi/jicofo/jicofo.conf

```

jicofo {
  authentication: {
    enabled: true
    type: XMPP
    login-url: jitsi-meet.example.com
  }
  ...
}

```

Prosody User

```

sudo prosodyctl register <username> jitsi-meet.example.com <password>

systemctl restart prosody
systemctl restart jicofo
systemctl restart jitsi-videobridge2

```

Branding

/etc/jitsi/meet/[your-hostname]-config.js dynamicBrandingUrl:
'/static/brand/branding.json', 가 .

nginx URL/static/

/usr/share/jitsi-meet/static/ branding

/usr/share/jitsi-meet/static/brand/branding.json

```

{
  "backgroundColor": "#FFF",
  "backgroundImageUrl": "https://mycompany.com/images/background.png",
  "didPageUrl": "https://mycompany.com/dids",
  "inviteDomain": "https://mycompany.com/invite",
  "logoClickUrl": "https://mycompany.com",
  "logoImageUrl": "https://mycompany.com/images/logo.png",
}

```

```
"avatarBackgrounds": ["#12A378", "linear-gradient(125.83deg, #000 0%, #FFF 99.09%)"],
"premeetingBackground":
"url(https://mycompany.com/images/premeetingBackground.png)",
"virtualBackgrounds": ["https://my.img01.jpg", "https://my.img02.jpg"],
"labels": {
  "en": "https://myenglishlabels.json",
  "fr": "https://myfrenchlabels.json",
  "ptBR": "https://mybrazilianlabels.json"
},
"customTheme": {
  "palette": {
    "ui01": "orange !important",
    "ui02": "maroon",
    "surface02": "darkgreen",
    "ui03": "violet",
    "ui04": "magenta",
    "ui05": "blueviolet",
    "field02Hover": "red",
    "action01": "green",
    "action01Hover": "lightgreen",
    "action02Disabled": "beige",
    "success02": "cadetblue",
    "action02Hover": "liceblue"
  },
  "typography": {
    "labelRegular": {
      "fontSize": 25,
      "lineHeight": 30,
      "fontWeight": 500
    }
  }
}
```

```
prosodyctl /
. /var/lib/prosody/*/accounts
가 .
```

```
ls /var/lib/prosody/*/accounts|grep .dat|sed s/'.dat'//g
```

가 가 .

```
curl -OJL http://prosody.im/files/mod_listusers.lua
```

```
chmod 755 mod_listusers.lua  
mv mod_listusers.lua /usr/lib/prosody/modules/
```

- <https://partage.les-miquelots.net/engver/blog/list-accounts-created-with-prosodyctl.html>

- <https://jitsi.github.io/handbook/docs/devops-guide/devops-guide-quickstart>
- <https://jitsi.github.io/handbook/docs/devops-guide/secure-domain>
- <https://developer.8x8.com/jaas/docs/jaas-prefs-advanced-branding>

From:

<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:

https://atl.kr/dokuwiki/doku.php/jitsi_meet_%EC%84%A4%EC%B9%98_%EB%A7%A4%EB%89%B4%EC%96%BC?rev=1671337169

Last update: 2022/12/18 04:19

