

JSESSIONID sessionCookieName	3
Tomcat 6.x	3
Tomcat 7.x	3
Tomcat 8.x	3

JSESSIONID sessionCookieName

Tomcat 6.x

- <http://tomcat.apache.org/tomcat-6.0-doc/config/systemprops.html>

가.

```
-Dorg.apache.catalina.SESSION_COOKIE_NAME=MYSESSIONID  
-Dorg.apache.catalina.SESSION_PARAMETER_NAME=MYSESSIONID
```

Tomcat 7.x

Context sessionCookieName attribute 가 .

```
<Context sessionCookieName="SESSIONID" cookies="true">
```

Tomcat 8.x

Web Application Servlet 3.0 (web.xml)

WebApplication web.xml session-config - cookie-config - name

```
<?xml version="1.0" encoding="UTF-8"?>  
<web-app xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"  
  xmlns="http://java.sun.com/xml/ns/javaee"  
  xsi:schemaLocation="http://java.sun.com/xml/ns/javaee  
http://java.sun.com/xml/ns/javaee/web-app_3_0.xsd"  
  id="WebApp_ID" version="3.0">  
  
  <display-name>LDS</display-name>  
  
  <welcome-file-list>  
    <welcome-file>index.html</welcome-file>  
    <welcome-file>index.htm</welcome-file>  
    <welcome-file>index.jsp</welcome-file>  
    <welcome-file>default.html</welcome-file>  
    <welcome-file>default.htm</welcome-file>  
    <welcome-file>default.jsp</welcome-file>  
  </welcome-file-list>  
  
  <filter>
```

```
<filter-name>Set Character Encoding</filter-name>
<filter-class>filters.SetCharacterEncodingFilter</filter-class>
<init-param>
  <param-name>encoding</param-name>
  <!-- <param-value>euc-kr</param-value> -->
  <param-value>UTF-8</param-value>
</init-param>
</filter>

<filter-mapping>
  <filter-name>Set Character Encoding</filter-name>
  <url-pattern>/*</url-pattern>
</filter-mapping>

<!-- Clustering context -->
<distributed />

<session-config>
  <cookie-config>
    <!--      Session Cookie Name      ,      -->
      mod-jk  session_cookie
    <name>MYSESSIONID</name>
    <!-- HttpOnly      :      가      ,      . -->
      <http-only>>true</http-only>
    <!-- Secure      : SSL      -->
      <secure>>true</secure>
  </cookie-config>
</session-config>
</web-app>

===== mod-jk      =====
mod-jk      sticky-session      worker      balancer
가      .

<WRAP prewrap>
<code vim>
worker.balancer.session_cookie=MYSESSIONID
```

From: <https://at1.kr/dokuwiki/> - AllThatLinux!
Permanent link: https://at1.kr/dokuwiki/doku.php/jsessionid_sessioncookie_name_%EB%B3%80%EA%B2%BD?rev=1607413886
Last update: 2020/12/08 07:51

