

JSESSIONID sessionCookieName	3
Tomcat 6.x	3
Tomcat 7.x	3
Tomcat 8.x	3
mod-jk	4

JSESSIONID sessionCookieName

Tomcat 6.x

- <http://tomcat.apache.org/tomcat-6.0-doc/config/systemprops.html>

가.

```
-Dorg.apache.catalina.SESSION_COOKIE_NAME=MYSESSIONID
-Dorg.apache.catalina.SESSION_PARAMETER_NAME=MYSESSIONID
```

Tomcat 7.x

Context sessionCookieName attribute 가 .

```
<Context sessionCookieName="MYSESSIONID" cookies="true">
```

Tomcat 8.x

Web Application Servlet 3.0 (web.xml)

WebApplication web.xml session-config - cookie-config - name

```
<?xml version="1.0" encoding="UTF-8"?>
<web-app xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns="http://java.sun.com/xml/ns/javaee"
  xsi:schemaLocation="http://java.sun.com/xml/ns/javaee
http://java.sun.com/xml/ns/javaee/web-app_3_0.xsd"
  id="WebApp_ID" version="3.0">

  <display-name>LDS</display-name>

  <welcome-file-list>
    <welcome-file>index.html</welcome-file>
    <welcome-file>index.htm</welcome-file>
    <welcome-file>index.jsp</welcome-file>
    <welcome-file>default.html</welcome-file>
    <welcome-file>default.htm</welcome-file>
    <welcome-file>default.jsp</welcome-file>
  </welcome-file-list>

  <filter>
```

```
<filter-name>Set Character Encoding</filter-name>
<filter-class>filters.SetCharacterEncodingFilter</filter-class>
<init-param>
  <param-name>encoding</param-name>
  <!-- <param-value>euc-kr</param-value> -->
  <param-value>UTF-8</param-value>
</init-param>
</filter>

<filter-mapping>
  <filter-name>Set Character Encoding</filter-name>
  <url-pattern>/*</url-pattern>
</filter-mapping>

<!-- Clustering context -->
<distributable />

<!-- . -->
<session-config>
  <!-- ( ) -->
  <session-timeout>30</session-timeout>
  <!-- -->
  <cookie-config>
    <!-- Session Cookie Name , -->
    mod-jk session_cookie -->
    <name>MYSESSIONID</name>

    <!-- HttpOnly : 가 , -->
    . -->
    <http-only>>true</http-only>

    <!-- Secure : SSL -->
    <secure>true</secure>
  </cookie-config>
  <!-- url ;jsessionid 가 -->
  <tracking-mode>COOKIE</tracking-mode>
</session-config>
</web-app>
```

mod-jk

mod-jk sticky-session worker balancer 가 .

```
worker.balancer.session_cookie=MYSESSIONID
```

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/jsessionid_sessioncookie_name_%EB%B3%80%EA%B2%BD?rev=1607426234

Last update: **2020/12/08 11:17**

