

* *

```

#                                     (max 65535)
# 128M -> 8192
# 256M -> 13684
# 512M -> 32768
# 1G -> 65536
# 2G -> 131072
fs.file-max = 65535

#          가          received host          backlog
net.core.netdev_max_backlog=2500

#
#          Serving
net.core.rmem_default = 65536
net.core.rmem_max = 8388608

#
#          Serving
#
net.core.wmem_default = 65536
net.core.wmem_max = 8388608

# TCP layer
#
net.ipv4.tcp_rmem = 4096 87380 8388608

# TCP layer
net.ipv4.tcp_wmem = 4096 65536 8388608

# The tcp_mem variable defines how the TCP stack should behave when it comes
to memory usage.
# TCP
#          min pressure max          . tcp_wmem tcp_rmem
# IA32 4KB가
#          가
# {min} {pressure} {max}
net.ipv4.tcp_mem = 4096 4096 4096

#
#          7          "TCP: too many of orphaned
sockets"
# "Out of socket memory"          가
net.ipv4.tcp_orphan_retries = 7

```

```

# RST TIME_WAIT 가
# 가
# net.ipv4.tcp_max_tw_buckets
net.ipv4.tcp_rfc1337 = 1

# SPECWeb99 selective
acknowledgements off
. SPECWeb99 1-2hop 가
on

# on
net.ipv4.tcp_sack = 1

# SPECWeb99 timestamps off
# SPECWeb99 1-2hop 가
# on . tcp_window_scaling
# on
net.ipv4.tcp_timestamps = 1

# tcp_sack tcp_timestamps
# , rmem, wmem tcp_rmem, tcp_wmem
# tcp_timestamps on
net.ipv4.tcp_window_scaling = 1

# KEEPALIVE stale
net.ipv4.tcp_keepalive_time = 1300

# listen backlog
net.ipv4.tcp_max_syn_backlog = 8192

# FIN_TIMEOUT
net.ipv4.tcp_fin_timeout = 30

# 가
net.ipv4.ip_local_port_range = 16384 65536

# DOS SYN flooding On
#
# tcp_
net.ipv4.tcp_syncookies = 1

# off IP
net.ipv4.ip_forward = 0

# high load
# TIME_WAIT 가 60 가

```

```

net.ipv4.tcp_max_tw_buckets = 2000000

# Linux 2.4
# ssthread

# 10

net.ipv4.route.flush = 1

# 가
# 가
vm.bdflush = 100 1200 128 512 15 5000 500 1884 2

# , ICMP ECHO . smurf
#
net.ipv4.icmp_echo_ignore_broadcasts = 1

# SRR . IP source routing
# . TRUE (router) FALSE (host)
#
net.ipv4.conf.all.accept_source_route = 0

#net.ipv4.conf.all.send_redirects=0
#net.ipv4.conf.all.accept_redirects=0
# DOS IP Spoofing Source Route
# 가
# on
# RFC182 IP spoof ( 2.2 )
#
net.ipv4.conf.eth0.rp_filter = 1
net.ipv4.conf.lo.rp_filter = 1
net.ipv4.conf.default.rp_filter = 1
net.ipv4.conf.all.rp_filter = 1

# Log Spoofed Packets, source Routed Packets, Redirect packetes
# ip
#
net.ipv4.conf.all.log_martians = 1

#
kernel.shmmax=3800000000

#
# : { SEM } { SEM } { SEMOP OP } { }
# : { SEM } = { } x { SEM } (DB2
)
kernel.sem=1000 32000 32 512

#
kernel.msgmni = 1024

```

From:

<https://atl.kr/dokuwiki/> - **AllThatLinux!**

Permanent link:

https://atl.kr/dokuwiki/doku.php/linux_kernel_parameter?rev=1422325914

Last update: **2015/06/18 15:49**

