

| LVM | Root Volume | VG | |
|-----|-------------|----|---------|
| | | | 3 |
| | | | 4 |

LVM Root Volume VG

1. vgrename VG

```
# vgrename oldvg newvg
```

2. lvrename

```
# lvrename /dev/newvg/oldlv /dev/newvg/newlv
```

3. VG LV /etc/fstab

```
/dev/mapper/newvg-newlv / xfs defaults 1 1
```

```
# systemctl daemon-reload
```

```
# vi /etc/default/grub
```

```
GRUB_CMDLINE_LINUX="rd.lvm.lv=newvg/newlv crashkernel=auto  
rd.lvm.lv=newvg/newlv1 vconsole.font=latarcyrheb-sun16 vconsole.keymap=us "
```

6. VG

```
# vgchange -ay
```

7. LV

```
# lvchange /dev/newvg/root --refresh  
# lvchange /dev/newvg/swap --refresh
```

8. initramfs

Last update: 2023/06/14 09:23 lvm_root_volume https://atl.kr/dokuwiki/doku.php/lvm_%EC%97%90%EC%84%9C_root_volume%EC%9D%98_vg_%EC%9D%B4%EB%A6%84%EC%9D%84_%EB%B3%80%EA%B2%BD%ED%95%98%EB%8A%94_%EB%B0%A9%EB%B2%95

```
# cp /boot/initramfs-$(uname -r).img /boot/initramfs-$(uname -r).img.$(date +%m-%d-%H%M%S).bak  
# dracut -v -f /boot/initramfs-$(uname -r).img $(uname -r)
```

9. grub2.cfg

grub2-mkconfig

grub

BIOS-based machines:

```
# cp /boot/grub2/grub.cfg /boot/grub2/grub.cfg.bak  
# grub2-mkconfig -o /boot/grub2/grub.cfg
```

UEFI-based machines:

```
# cp /boot/efi/EFI/redhat/grub.cfg /boot/efi/EFI/redhat/grub.cfg.bak  
# grub2-mkconfig -o /boot/efi/EFI/redhat/grub.cfg
```

grub

가

LVM VG

```
/usr/sbin/grub2-probe: error: failed to get canonical path of  
'/dev/mapper/rhelnew1-root'.
```

- <https://access.redhat.com/solutions/1573673>

From:
<https://atl.kr/dokuwiki/> - AllThatLinux!

Permanent link:
https://atl.kr/dokuwiki/doku.php/lvm_%EC%97%90%EC%84%9C_root_volume%EC%9D%98_vg_%EC%9D%B4%EB%A6%84%EC%9D%84_%EB%B3%80%EA%B2%BD%ED%95%98%EB%8A%94_%EB%B0%A9%EB%B2%95

Last update: 2023/06/14 09:23

